

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 December 2002 (27.12.2002)

PCT

(10) International Publication Number
WO 02/102254 A2

(51) International Patent Classification⁷: **A61B 17/16**,
A61F 2/38

(21) International Application Number: PCT/US02/18742

(22) International Filing Date: 14 June 2002 (14.06.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/882,591 14 June 2001 (14.06.2001) US
10/075,829 12 February 2002 (12.02.2002) US

(71) Applicants and

(72) Inventors: ENGH, Gerard [US/US]; 9409 Ludgate
Drive, Alexandria, VA 22309 (US). JOHNSON, Wesley,
D. [US/US]; 8091 Spruce Trail, Eden Prairie, MN 55347
(US).

(74) Agents: BAUMAN, Mary, P. et al.; Fredrikson & Byron,
P.A., 1100 International Centre, 900 2nd Ave. S., Min-
neapolis, MN 55402-3397 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,
SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA,
ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS AND METHOD FOR SCULPTING THE SURFACE OF A JOINT



(57) Abstract: The present invention provides a method and device for restoring individual patient joint kinematics using minimally invasive surgical procedures. The instrumentation of the invention sculpts the articular surface of a first bone that normally articulates in a predetermined manner with a second bone. The instrumentation includes a bone sculpting tool and a mount for attaching the tool to the second bone. The implant system is comprised of implants that provide intraoperative surgical options for articular constraint and facilitate proper alignment and orientation of the joint to restore kinematics as defined by the individual patient anatomy.

WO 02/102254 A2

5

**APPARATUS AND METHOD FOR SCULPTING THE
SURFACE OF A JOINT**Background of the Invention

10 A joint, such as the ankle, knee, hip or shoulder, generally consists of two or more relatively rigid bony structures that maintain a relationship with each other. Soft tissue structures spanning the bony structures hold the bony structures together and aid in defining the motion of one bony structure to the other. In the knee, for example, the bony structures are the tibia and the femur. Soft tissue such as ligaments, tendons, menisci, and capsule provide support to the tibia and femur. A
15 smooth and resilient surface consisting of articular cartilage covers the bony structures. The articular surfaces of the bony structures work in concert with the soft tissue structures to form a mechanism that defines the envelop of motion between the structures. Within a typical envelop of motion, the bony structures move in a predetermined pattern with respect to one another. When fully articulated, the
20 motion defines a total envelop of motion between the bony structures. In the knee, the soft tissue structures spanning the joint tend to stabilize the knee in a transverse plane. This transverse stability enables the bony structures to slide and rotate on one another in an orderly fashion.

The articular surfaces are subject to a variety of diseases, accidents and the
25 like that cause the surfaces to be damaged. A common disorder of joints is degenerative arthritis. Degenerative arthritis causes progressive pain, swelling, and stiffness of the joints. As the arthritic process develops, the joint surfaces wear away, resulting in contractures of the surrounding soft tissues that provide stability to the joint. Changes in the articular surfaces resulting from arthritis decrease stability
30 and increase the translation of the joint.

Treatment of the afflicted articular bone surfaces depends, among other things, upon the severity of the damage to the articular surface and the age and general physical robustness of the patient. The end result commonly necessitates joint replacement surgery wherein the articulating elements of the joint are replaced
35 with artificial elements commonly consisting of a part made of metal articulating with a part made of ultra high molecular weight polyethylene (UHMWPE).

5 A relatively young patient with moderate to severe degeneration of the knee joint is often treated with drug therapies. While drug therapies may temporarily provide relief of pain, progression of the disease, with resulting deformity and reduced function, ultimately necessitates surgery. Alternative treatments such as nonsteroidal anti-inflammatory drugs, cortisone injections, and arthroscopic
10 debridement similarly provide only temporary relief of symptoms.

 In severe situations, the entire articular surface of a bone may be replaced with an artificial surface, as, for example, when condyles at the distal end of the femur are largely replaced with a prosthetic device having polished metal condyles and the tibial plateau is replaced with a plastic bearing that may be supported by a
15 metal component. Joint replacement surgery has become a proven and efficacious method of alleviating pain and restoring function of the joint.

 Current methods of preparing the intra-articular rigid elements of a joint to receive components as in joint replacement surgery involve an extensive surgical exposure. The exposure must be sufficient to permit the introduction of guides that
20 are placed on, in, or attach to the joint, along with cutting blocks to guide the use of saws, burrs and other milling devices, and other instruments for cutting or removing cartilage and bone that subsequently is replaced with artificial surfaces. For knee joint replacement, the distal end of the femur may be sculpted to have flat anterior and posterior surfaces generally parallel to the length of the femur, a flat end surface
25 normal to the anterior and posterior surfaces, and angled flat surfaces joining the above mentioned surfaces, all for the purpose of receiving a prosthetic device. For total hip replacement, the acetabular articular surface and subchondral bone is removed by spherical reamers, the femoral head is resected with an oscillating saw, and the proximal medullary canal is shaped with broaches. A difficulty with total hip
30 replacement is that the invasiveness of the procedure causes significant intraoperative blood loss and extensive rehabilitation because muscles and tendons must be released from the proximal femur to mobilize the femur and gain exposure of and access to the acetabular fossa.

 A full joint replacement, using the example of the knee joint, also requires the
35 proximal end of the tibia to be sculpted to receive a prosthesis having a generally upwardly facing bearing surface mimicking the normal tibial bearing surface and designed to articulate with the condylar surfaces of the femoral prosthesis. Typically,

5 this surgery is performed with instruments or guides to orient cutting blocks, such that the preparation of the bone is in concordance with the correct alignment of the limb and the parts are correctly oriented in both coronal and sagittal positions. The guides are placed on exposed bones and generally reference anatomical points on that bone to establish a resection plane. For instance, with total knee replacement,
10 arthroplasty guides are used by referencing, for example, the intramedullary cavity and the epicondylar and posterior condylar axes.

Knee joint prosthesis of the type referred to above are well known, and are described, for example, in Caspari et. al., U.S. patents 5,171,244, 5,171,276 and 5,336,266, Brown, U.S. patent 4,892,547, Burstein et al., U.S. patent 4,298,992, and
15 Insall et. al., U.S. patent 6,068,658.

Substantial effort has been made to provide appropriate degrees of curvature to the condyles in knee joint replacement. For example, the earlier mentioned U.S. patents 5,171,276, 4,298,992 and 6,068,658 show that the radius of curvature in the anterior-posterior direction of the condyle of a femoral prosthesis may be somewhat
20 greater near the anterior portion of the condyle than near the posterior portion. Kester et al., U.S. Patent 5,824,100 teaches that a portion of this curvature of the condyle may be formed about a constant radius having its origin along a line between the lateral and medial collateral ligament attachment points on the femur.

Historically, a variety of modular prosthetic joint implants have been
25 developed. The following descriptions of modular implants relate specifically to the knee. Early designs for knee implants, called polycentric knee implants, were developed with separate components for the medial and lateral compartments. Additionally, modular fixed-bearing knee implants having a polyethylene insert that is held relatively rigidly in place have been developed. Alternately, there are mobile
30 bearing knee implants wherein the polyethylene bearing is designed to slide or move with minimal or no constraint on a tibial baseplate. Furthermore, both meniscal bearing and fixed bearing knee implants have been developed including either separate polyethylene bearings or a single polyethylene bearing that resides on a metallic tibial baseplate. While implant systems have been developed with fixed
35 bearing elements or mobile bearing elements on the medial and lateral sides of the tibiofemoral joint, systems have not been developed having a combination of a fixed bearing on one side and a mobile bearing on the other side of the tibiofemoral joint.

5 Mobile bearing tibial implants may be configured to be more congruent with
the femoral side of a knee arthroplasty, yielding lower contact stress. The resultant
lower contact stress reduces the possibility of damage sometimes encountered with
some fixed bearing designs wherein the yield strength of the bearing material is
exceeded. In general, fixed bearing implant designs are less difficult to properly
10 align and balance than mobile bearing designs. Mobile bearing designs are
frequently desirable to reduce contact stress and the resulting wear of the bearing
surface. However, with mobile bearing designs, there is the possibility of the bearing
becoming dislodged from the implant. Additionally, mobile bearing knee designs are
more surgically demanding to implant than fixed bearing designs.

15 The combination of a fixed bearing insert for the medial compartment and a
mobile bearing insert for the lateral compartment is particularly attractive because
the lateral femoral condyle rolls backward on the lateral tibial plateau as much as 10
to 20 millimeters whereas the medial condyle moves only a few millimeters. A mobile
bearing insert is able to accommodate the rollback of the lateral condyle but would
20 not be necessary for the medial condyle.

Two primary difficulties exist with current joint replacement surgeries. These
relate to the invasiveness of the procedure and achieving proper alignment of the
bony structures and the prostheses thereupon. Such difficulties are present in all
total joint replacements, including ankle, knee, hip and shoulder. Total knee and
25 total hip arthroplasty are described as general examples of the difficulties in current
joint replacement surgery.

Alignment. A difficulty with implanting both modular and non-modular knee
implants having either separate femoral and/or tibial components has been achieving
a correct relationship between the components. Surgical instruments available to
30 date have not provided trouble free use in implanting multi-part implants wherein the
femur and tibia are prepared for precise component-to-component orientation. While
alignment guides aid in accurate orientation of the components relative to the axis of
the long bones to achieve a restoration of a correct tibiofemoral alignment (usually 4-
7 degrees valgus), they provide limited positioning or guidance relevant to correct
35 component-to-component alignment and/or ligament tension to restore alignment.

5 It is preferable to orient implants normal to the resultant forces through the joint to subject bearing surfaces to compressive rather than shear forces. Moreover, the components of the implant are preferably oriented one to the other to minimize wear. Complications may result if the implant is not correctly oriented with respect to the supporting bone. If the implant is not placed normal to the mechanical axis, a
10 shearing force results between the implant and bone that may lead to implant loosening.

 In a properly aligned knee, the mechanical axis of the leg (a straight line drawn from the center of the hip joint to the center of the ankle) passes slightly medial to the center of the knee. This alignment is generally called the gross
15 alignment of the leg. The alignment of the implants impacts the gross alignment of the leg. If the implants are malaligned, the resulting mechanical axis may be shifted medially or laterally, resulting in an imbalance in the loads carried by the medial or lateral condyles. This imbalance, if severe, may lead to early failure of the implant.

 In addition, the orientation of the components to each other, for example the
20 orientation of the femoral component to a second and or third femoral component, orientation of a tibial component to a separate second tibial component and orientation of a femoral component to its corresponding tibial component, with unicondylar and bicondylar implants has largely not been addressed. This may account for the high failure rates of early bicondylar designs and as well as for the
25 higher failure rate of unicondylar implants relative to total knee implants as demonstrated in some clinical studies. When considering bicondylar and unicondylar designs, alignment of each part relative to the other parts is critical to avoid accelerated wear with a mal-articulation of the components.

 Although various prosthetic devices have been successfully used with
30 patients, the configuration and position of the articulating surfaces of the prosthesis, for example the condyles in a knee joint, are predetermined based upon the prosthesis that is selected. While efforts are made to tailor the prosthesis to the needs of each patient by suitable prosthesis choice and size, this in fact is problematical inasmuch as the joint physiology of patients can vary substantially
35 from one patient to another.

5 **Invasiveness.** In order to appropriately sculpt the articulating surface of a bone, it is often necessary to surgically expose the joint. In the case of the femur in traditional knee joint replacement, the patellar tendon of the knee joint is surgically exposed and is moved to one side of the joint to enable a substantially full anterior access to the joint. Surgical exposure is necessary to accommodate the bulk and
10 geometry of the components as well as the instruments for bone preparation. Such surgical exposure increases bleeding, pain, and muscle inhibition; all of which contribute to a longer hospitalization before the patient can be safely discharged to home or an intermediate care facility.

Desirably, in the case of knee replacement surgery, neither the collateral
15 ligaments nor the cruciate ligaments are disturbed, although it is often necessary to remove or release cruciate ligaments in the event a substantial joint replacement is to be performed. Collateral ligaments can be partially taken down or released to provide appropriate tension adjustment to the patient's knee in concert with joint replacement surgery. In most instances, such releases can be accomplished
20 through smaller incisions than the standard midline or medial parapatellar incisions historically used for knee arthroplasty.

Arthroscopic surgery is available, and beneficial, for removing and repairing damaged intraarticular tissues. Although arthroscopic procedures are far less invasive and are often successful for minor surgical repairs, (as when an articular
25 surface is to be smoothed, for example, or cartilage is to be repaired), such procedures generally are not appropriate for substantial joint replacement. They are generally inadequate for replacing joint surfaces with artificial implants.

Conventional surgical procedures including unicompartmental and total joint replacement historically required extensive surgical exposure and prolonged hospital
30 stays and rehabilitation. More recently, unicondylar knee joint replacement procedures have been performed through smaller incisions that do not necessitate dislocation of the patella. The reduction in pain and more rapid recovery of knee function has reduced the length of hospital stay and the need for strong narcotic medications. It is desirable to realize such benefits for patients with bicompartamental
35 and tricompartmental knee arthroplasty.

5 As in the knee, conventional total hip arthroplasty is indicated for painful
arthritis of the hip joint. The procedure involves exposing the hip joint through a
large incision to provide the surgeon full visualization of the hip joint and the
acetabular region and to provide access for surgical power instruments. In order to
appropriately prepare the bony structures of the hip joint, the major muscles
10 spanning the joint are commonly disrupted to gain adequate exposure of the joint.
Steps of the procedure include removing the femoral head followed by reaming and
broaching the proximal femoral canal to prepare a bony surface to support a hip
stem. The stem is implanted and may be cemented in place, or press fit for bony
ingrowth. The acetabulum is typically prepared using a hemispherical reamer to
15 remove cartilage down to bleeding bone. Once the acetabulum is prepared, an
acetabular component is implanted, either by cementing in place or press fitting for
bony ingrowth. The surgical exposure, which may be between six and twelve inches
in length, may result in extensive trauma to the soft tissues surrounding the hip joint
along with the release of muscles that insert into the proximal femur.

20 The prepared bony surfaces are technically referred to as the acetabular
fossa, femoral canal and metaphyseal region of the femur. Prior to placing final
implants into the prepared spaces, a femoral trial, which may be a broach in some
systems, is placed in the proximal femur along with a trial femoral head and neck,
and an acetabular trial is placed into the acetabulum to facilitate trial range of motion
25 and evaluation of hip stability prior to placement of the final total hip implants.

A system to enable minimally invasive total hip arthroplasty that will minimize
soft tissue trauma and accelerate postoperative rehabilitation is needed. Further,
because minimally invasive techniques inherently limit observation of the surgical
site, compromising visualization of the prepared bony surfaces, a device is also
30 needed for inspection of the prepared bony surfaces. During a surgical procedure,
bone debris and blood will gather in the surgical site and require removal from time
to time to visualize the acetabulum. After preparation of the acetabulum, an
acetabular component is implanted. A variety of acetabular components such as
cemented UHMWPE cups, cemented or press fit metal shells with UHMWPE, metal,
35 or ceramic bearing liners are presently used. Typically, placement of a press fit shell
requires an impaction force to fully seat the implant into support bone. However, the
size and location of the minimally invasive incision may not be optimal for proper

5 orientation and application of force to adequately seat and stabilize an acetabular implant. Thus, an impaction device is needed that allows for impaction of the acetabular component with the hip reduced or articulated for use with a minimally invasive exposure for total hip arthroplasty. It may also be desirable to use a surgical navigation system to prepare the joint surfaces and position the implants.

10 For patients who require articular surface replacement, including patients whose joints are not so damaged or diseased as to require whole joint replacement, it is desirable to provide surgical methods and apparatuses that may be employed to gain surgical access to articulating joint surfaces, to appropriately prepare the bony structures, to provide artificial, e.g., metal or plastic, articular bearing surfaces, and
15 to close the surgical site, all without substantial damage or trauma to associated muscles, ligaments or tendons. To attain this goal, a system and method is needed to enable articulating surfaces of the joints to be appropriately sculpted using minimally invasive apparatuses and procedures.

Summary of the Invention

20 The present invention provides a system and method for total joint replacement that involves minimally invasive surgical procedures including an implant system that restores individual patient joint kinematics. The instruments and implants disclosed accomplish accurate bone and soft tissue preparation, implant orientation and implant fixation through limited surgical exposure.

25 Thus, in one embodiment, the present invention provides a method of appropriately sculpting the articular surface of a first bone that normally articulates with a second bone and implanting a prosthetic device. The method involves attaching a bone sculpting tool directly or indirectly to the second bone with the tool in bone sculpting engagement with the articular surface of the first bone, and then
30 sculpting the articular surface of the first bone with the joint reduced and if indicated moving one bone with respect to the other. Optionally, the bone sculpting tool may be attached to a mount that is attached directly or indirectly to the second bone. In some situations, it may be desirable to distract the first bone from the second bone during surgery. The bone sculpting tool may also be attached to a bone mount that
35 is directly or indirectly attached to or integral with a stem, trial, reamer or broach implanted in the medullary canal of a bone.

5 For knee joint replacement, the implant system is comprised of implants and instrumentation that provide intraoperative surgical options for articular constraint and facilitate proper alignment and orientation of the knee to restore kinematics as defined by the individual patient anatomy. To do so, the implants provide a surgeon intraoperative options to reconstruct various degrees of joint stability via selection of
10 fixed or mobile bearing components for each compartment of the knee (medial tibiofemoral joint, lateral tibiofemoral joint and patellofemoral joint). The range of implants may cover only one compartment or each compartment of the knee and may include combinations of fixed and mobile bearing configurations.

15 In traditional total knee replacements, the femoral component is generally a unitary piece and the tibial component is a unitary piece. In the current invention, the femoral side may be resurfaced by two or three components and the tibial side may be resurfaced by two components or a unitary piece. The components may be aligned and or joined one to another within the confines of the joint. Optionally, the components of the femoral side may be comprised of a plurality of flexible segments.

20 Proper alignment and positioning of the implant components is facilitated by instrumentation that utilizes the soft tissue structures of the knee to guide bony resections for patient-specific alignment and orientation of the implants. Alignment of the implants with respect to the supporting bones relates to restoring or improving the anatomical alignment of the supporting bones. Orientation of the implants with
25 respect to the supporting bones is significant in two ways. First, orientation of the implant construct with respect to the supporting bones is such that the forces transferred through the implant are generally normal or perpendicular to the bony support surfaces. Second, orientation of the implant components with respect to one another is such that each modular component restoring the femoral articular
30 surfaces is properly aligned with the other modular components on the femoral side to ensure proper tracking of the implant construct. Likewise, each modular component restoring the tibial articular surfaces is properly aligned with other modular components on the tibial side to ensure proper tracking of the implant construct. The surgical instrumentation prepares the articular surfaces of a synovial
35 joint from a single point of reference to allow the introduction of separate components for the medial and lateral tibiofemoral compartments, and the patellofemoral compartments with precise orientation. Thus, the instrumentation

- 5 provides bony resections in accordance with such alignment and orientation requirements. The positioning is important for proper restoration of anatomic alignment of the knee joint and for proper orientation of the components to one another.

10 With respect to forming or sculpting articular surfaces of a joint, the method of the current invention enables the articular bone surfaces to be sculpted according to the individual physiology of each patient to restore as much as possible the natural junction of the joint. In this method, a bone sculpting tool is attached to one of the bones of a joint, and the tool sculpts the articular surface of the other bone as the joint is articulated.

- 15 Thus, in one embodiment, the present invention provides a method of appropriately sculpting the articular surface of a first bone that normally articulates with a second bone. The method involves providing an apparatus comprising a bone sculpting tool attached to a bone mount, attaching the mount rigidly to the second bone with the tool in bone sculpting engagement with the articular surface of the first bone, and then sculpting the articular surface by articulating one of the bones with respect to the other.

25 In some situations, it may be desirable to distract the first bone from the second bone, either preoperatively or during surgery. Thus, a distractor may be provided with the apparatus. In knee joint replacement, a distraction force provided between the femur and the tibia during the sculpting procedure accounts for material that has worn away from the articular surfaces. Use of a distraction force generally re-establishes normal alignment of the joint. Ligament releases may be carried out to restore alignment either prior to preparing the joint surfaces or following the preparation of the joint surfaces with bone sculpting instruments. Additionally, a distractor may be used preoperatively to assess the range of motion of the joint and patient kinematics.

- 30 In another embodiment, the invention provides an apparatus for sculpting the articular surface of a first bone that normally articulates in a predetermined manner with a second bone. The apparatus comprises a bone sculpting tool, a mount attachable rigidly to the second bone, and an adjustable attachment attaching the sculpting tool to the mount and enabling the position and orientation of the tool to be

5 adjusted into bone-sculpting proximity to the articular surface so that the articular surface is sculpted as the second bone is articulated with respect to the first bone. Alternately, a plurality of bone sculpting tools may be used where the tools are positioned either on individual mounts or on a single mount to support the plurality of tools.

10 The invention also provides implants for replacing the surfaces of the joint between the first bone and the second bone. The implants are specifically designed to fit through minimally invasive incisions and incorporate any and all combinations of fixed and mobile bearing inserts or parts. Since the surgical procedure preferably is performed through minimally invasive incisions the implants are designed to fit
15 through such incisions and be either oriented or joined within the joint.

In the case of knee replacement surgery, the implants include a second bone baseplate and a first bone implant. The second bone baseplate may be either one piece to cover most of the prepared surface of the second bone as relates to the joint, or separate baseplates as have been used with mobile and fixed bearing
20 prosthetic components. In addition, the second bone baseplate may accommodate separate fixed and mobile bearing inserts. The first bone implant is comprised of a plurality of components to replace the bearing surface of the first bone. Optionally, a portion of the first bone implant may be configured of a plurality of flexible segments bonded in place. Such a configuration permits the articulation of the second bone to
25 the first bone to mould the flexible segments in appropriate position.

Thus, in a further embodiment, the invention provides a method of appropriately replacing the articular surface of a first bone that normally articulates with a second bone. The method involves providing an apparatus comprising a bone sculpting tool attached to a bone mount, attaching the mount rigidly to the second
30 bone with the tool in bone sculpting engagement with the articular surface of the first bone, and then sculpting the articular surface by articulating one of the bones with respect to the other. Further, the articular surfaces are resurfaced with appropriate minimally invasive implants wherein the implants are joined within the confines of the joint cavity. In one embodiment, a plurality of flexible segments are provided to
35 resurface a portion of the first bone. The flexible segments are set in an adhesive along the resected surface of the first bone.

5 Specifically, for example in knee joint replacement, the invention may be used for replacing the surfaces of a femur and a tibia. Thus, a femoral implant having a plurality of components and a tibial baseplate are provided. The tibial baseplate may have a fixed bearing attachment as well as a mobile bearing attachment.

10 When applied to total hip joint replacement, the invention may be used for replacing the surfaces of a femur and acetabulum through a minimal incision and with minimal disruption of musculotendinous structures about the hip. A typical incision for a minimally invasive total hip procedure is between two and four inches in length. It is noted that there may be some variation in incision length due to patient physiology, surgeon preferences, and/or other factors; the stated range is illustrative,
15 not limiting. In addition to a small incision, care is taken to approach the joint capsule by separating tissues between muscle groups, rather than sectioning specific muscles.

 In total hip replacement, an acetabular component, such as a press fit shell, is implanted following preparation of the acetabulum. An impaction device is provided
20 that allows for impaction of the acetabular component with the hip reduced or articulated in order to fully seat a press fit acetabular component into support bone of the acetabulum. A surgical navigation system for positioning the acetabular component may be used with the impaction device.

 In the minimally invasive procedure, the hip is accessed through an incision
25 adequate to expose the trochanteric fossa and allow resection of the femoral neck and removal of the femoral head and neck segment. The femoral canal is accessed through the trochanteric fossa and trochanteric region. Reamers, rasps and other devices as are known to those skilled in the art are used to prepare the proximal femur to receive a femoral implant by a sequence of reaming and broaching steps.
30 Once prepared, the intramedullary canal and retained area of the femoral neck and trochanteric region are used to support the MIAR (Minimally Invasive Acetabular Reamer) system to prepare the acetabulum.

Brief Description of the Drawings

 Figure 1 shows a plan view of knee joint.

35 Figure 2 shows a traditional midline incision for accessing the knee joint during total knee replacement surgery.

5 Figure 3 shows an incision for accessing the knee joint during total knee replacement surgery that may be used with the method and apparatus of the present invention.

 Figure 4 shows alternate incisions for accessing the knee joint during total knee replacement surgery that may be used with the method and apparatus of the
10 present invention.

 Figure 5 illustrates a cross-sectional view of the cavity created in the tibial plateau in accordance with one embodiment of the present invention.

 Figure 6 shows a plan view of an instrument for creating a resection in the tibial plateau according to one embodiment of the present invention.

15 Figure 7 shows an end view of the instrument of Figure 6.

 Figure 8 shows a plan view of an instrument for creating a resection in the tibial plateau according to a second embodiment of the present invention.

 Figure 9 shows an end view of the instrument of Figure 8.

 Figure 10 shows a plan view of tibial resections formed in accordance with the
20 present invention.

 Figure 11 shows a top view of the resections shown in Figure 10.

 Figure 12 shows a cross-sectional view of one of the resections shown in Figure 10.

 Figure 13 shows a plan view of one embodiment of the present invention
25 having a cutting element attached to a tibial resection.

 Figure 14 shows a side view of a configuration of the cutting element of Figure 13 connected to a motor according to an alternate embodiment of the present invention.

 Figures 15 and 16 show alternate views of a cutting element driven by a
30 hydraulic motor in accordance to one embodiment of the present invention.

 Figures 17 and 18 show alternate views of a cutting element driven by a hydraulic motor in accordance to an alternate embodiment of the present invention.

 Figure 19 shows an end view of a cutting element in accordance with one embodiment of the present invention.

35 Figure 20 shows a side view of the cutting element of Figure 19.

 Figure 21 shows an end view of a cutting element in accordance with a second embodiment of the present invention.

 Figure 22 shows a side view of the cutting element of Figure 21.

5 Figure 23 shows an end view of a cutting element in accordance with a third embodiment of the present invention.

 Figure 24 shows a side view of the cutting element of Figure 23.

 Figure 25 shows a side view of a cutting element in accordance with a fourth embodiment of the present invention.

10 Figure 26 shows an end view of the cutting element of Figure 25.

 Figure 27 shows a cross-sectional view of the cutting element of Figure 25.

 Figure 28 shows an end view of a cutting element in accordance with a fifth embodiment of the present invention.

 Figure 29 shows a cross-sectional view of the cutting element of Figure 28
15 with a single cutting element.

 Figure 30 shows a cross-sectional view of the cutting element of Figure 28 with multiple cutting elements.

 Figure 31 illustrates the kinematics of the articulation of the knee joint in accordance with an embodiment of the present invention.

20 Figure 32 shows a plan view of two cutting element linked by a hinge mechanism according to an embodiment of the present invention.

 Figure 33 shows a plan view of an alternate state of the two cutting element linked by a hinge mechanism of Figure 32.

 Figure 34 shows a plan view of two cutting elements linked by a hinge
25 mechanism in accordance with another embodiment of the present invention.

 Figure 35 shows a plan view of the cutting elements of Figure 34.

 Figure 36 shows a plan view of two cutting elements linked by a hinge mechanism deployed in the knee joint according to an embodiment of the present invention.

30 Figure 37 shows a sectional view of a cutting element and distractor according to one embodiment of the present invention.

 Figure 38 shows a top view of the cutting element of Figure 37.

 Figure 39 shows a plan view of distractors deployed in the knee joint according to an embodiment of the present invention.

35 Figure 40 shows a plan view of femoral resections made in accordance with an embodiment of the present invention.

 Figure 41 shows a plan view of femoral resections made in accordance with an alternate embodiment of the present invention containing femoral implants.

5 Figure 42 shows a plan view of femoral resections made in accordance with a yet another embodiment of the present invention containing femoral implants.

 Figure 43 shows plan views of alternate embodiments of tibial baseplates in accordance with an embodiment of the present invention.

 Figure 44 shows a plan view of femoral implants for resurfacing the femoral resections of Figure 38k according to an embodiment of the present invention.

 Figure 45 shows a plan view of femoral implants for resurfacing the femoral resections of Figure 41 according to an embodiment of the present invention.

 Figure 46 shows a plan view of a femoral implant in accordance with an embodiment of the present invention.

15 Figure 47 is an illustration of hip anatomy and conventional exposure for total hip replacement;

 Figure 48 is an illustration of exposure for minimally invasive total hip replacement with reamer;

 Figure 49 is an illustration of a minimally invasive acetabular reamer in accordance with one embodiment of the present invention;

 Figure 50 is a cross sectional view of a minimally invasive acetabular reamer in a sagittal plane in accordance with one embodiment of the present invention;

 Figure 51 is a cross sectional view of a minimally invasive acetabular reamer cross in a transverse plane in accordance with one embodiment of the present invention;

 Figure 52 is an illustration of a minimally invasive acetabular reamer with an integral hydraulic drive in accordance with a further embodiment of the present invention;

 Figure 53 is an illustration of a minimally invasive acetabular reamer with a worm gear drive mechanism in accordance with yet another embodiment of the present invention;

 Figure 54 is an expanded view of a minimally invasive acetabular reamer in accordance with one embodiment of the present invention;

 Figure 55 is an illustration of illumination, visualization, irrigation and suction of an operative site in accordance with one aspect of the present invention;

5 Figure 56 is an illustration of a minimally invasive impaction system in accordance with one embodiment of the present invention; and

 Figure 57 is a detailed depiction of a minimally invasive impactor in accordance with one embodiment of the present invention.

Detailed Description of the Preferred Embodiment

10 **Knee Joint Anatomy and Surgical Approaches.** Figure 1 illustrates the general anatomy of the knee joint. The femur 10 has the lateral femoral condyle 12 and the medial femoral condyle 14 on its knee-joint articulating surface. The tibia 16 has the lateral meniscus 22 (generally opposite the lateral femoral condyle 12) and the medial meniscus 20 (generally opposite the medial femoral condyle 14) on its
15 knee-joint articulating surface. The ligaments include the anterior cruciate ligament 24, the posterior cruciate ligament 28, the medial collateral ligament 26 and the lateral collateral ligament 27. The medial tibial condyle 30 and the lateral tibial condyle 32 support the menisci 20 and 22, which in turn support the femur 10. Additionally, the fibula 34 engages the tibia 16.

20 Typically, a total knee joint replacement involves replacing the articular surfaces of the lateral femoral condyle 12, the medial femoral condyle 14, the medial tibial condyle 30 and the lateral tibial condyle 32. The lateral meniscus 22, and the medial meniscus 20 are removed. Desirably, neither the collateral ligaments 26 and 27 nor the cruciate ligaments 24 and 28 are disturbed. However, the collateral
25 ligaments 26 and 27 may be partially taken down to provide appropriate tension adjustments to the patient's knee after joint replacement has been completed.

 Figure 2 illustrates the conventional midline incision 40 for a total knee replacement surgery. The incision 40 extends vertically substantially above and below the articulating surface between the femur and the tibia. Typically, the incision
30 is roughly 8 to 15 centimeters in length. The incision 40 must be large enough to expose the entire knee joint articular surfaces with the patella subluxed or dislocated. Additionally, the incision must accommodate insertion of components that fully cover the end of the femur, the top of the tibia and the undersurface of the patella. The maximum number of components implanted would include femoral and tibial
35 components for the lateral tibiofemoral compartment, femoral and tibial components for the medial tibiofemoral compartment and femoral and patellar components for the

- 5 patellofemoral joint. Alternatively, the lateral femoral condyle and the patellar groove may be covered by a common implant.

As seen in figure 3, a transverse incision 42 extending horizontally along the knee joint is one option for the procedure of the present invention. The incision 42 may be vertically opened to expose the joint surfaces of the medial tibiofemoral
10 compartment and the lateral tibiofemoral compartment without dislocating the patella. This maintains the patella in contact with the femur during the procedure. The components of the instrumentation as well as the implant are sized for minimal invasiveness and, therefore, may be accommodated by the small incision. The reduced trauma resulting from a smaller incision generally results in faster and better
15 rehabilitation, which in turn generally increases the efficacy of the knee implant.

Figure 4 depicts an alternate incision format for use with the present invention. Two parallel vertically extending incisions 44 and 46 may be formed on either side of the patella. These incisions 44 and 46 are relatively short and the invasiveness is similar to that of the horizontal incision in figure 3. Each incision 44
20 and 46 is separately extended through the joint capsule to expose the medial and lateral tibiofemoral compartments without dislocating the patella.

Instrumentation. The instrumentation of the current invention, as related to total knee replacement, generally calls for resecting the tibia at the lateral tibial plateau and the medial tibial plateau. Optionally the instrumentation can be used to resect
25 the distal femur thereby creating an extension space to accommodate bone sculpting instrumentation. This resection may be done by methods known by those skilled in the art, using a resection guide, saw, etc. Alternately, as shown in Figure 5, a milling burr 43 may be advanced directly into the tibia 16. The milling burr 43 should stop at or short of the posterior cortical wall 54. Figure 5 shows a cross sectional view
30 through the cavity created in the tibial plateau by the milling burrs 47 of Figures 6 and 7.

As seen in Figures 6 and 7, the cutting device may be a single milling burr 45 affixed at the forward end of a guide element 49. The milling burr 45 of Figures 6 and 7 has its axel in a medial to lateral direction when preparing the tibial plateau.
35 The radius of the milling burr leaves a corresponding radius between the floor and posterior wall of the cavity created.

5 Alternately, as seen in Figures 8 and 9, the cutting device may comprise a plurality of milling burrs 47. The milling burrs 47 of Figures 8 and 9 prepare a corner between the floor and posterior wall of the cavity created in the tibial plateau. The corner thus prepared may distribute stress uniformly into the supporting bone. The milling burrs 47 create a radius equivalent to the radius of the burr between the
10 sidewalls of the cavity and the posterior wall. Such a radius is easily accommodated by the tibial implant design. While Figures 8 and 9 depict a cutting device having a plurality of milling burrs, the cutting device may be configured with one milling burr.

Figure 10 shows an anterior view of the bone resections 50 and 52 that are made in the tibial plateau, generally 51. The floor of the medial resection 50 and the
15 floor of the lateral resection 52 are preferably parallel and co-planar to ensure proper alignment and orientation of the medial and lateral tibial components. The external tools used to guide the tibial cutter may provide relative alignment between the medial and lateral resections. Alternately, the medial and lateral cavities in the tibial plateau may be prepared simultaneously by having two guide elements 49 linked
20 together by a hinge that restrains the medial and lateral milling burrs 47 in a common plane. The external tools may further provide a positive reference to the posterior aspect of the tibial plateau to ensure that the resections do not penetrate the posterior cortical wall. In Figure 10, the bone resections are shown to have a generally rectangular cross-section. However, any cross-section to which a bone
25 sculpting tool may be mounted may be used. For example, an arcuate cross-section is acceptable.

Figure 11 shows a top-view of bone resections 50 and 52 in the tibia 16. A cross-sectional view of the tibia 16 with a cavity machined into the plateau is depicted in Figure 12. As seen in Figure 12, the bone resection 50 should stop at or
30 short of the posterior cortical wall 54.

As seen in Figure 13, upon resection of the tibia, a bone sculpting tool, for example, a femoral cutter, generally 60, is placed in a mount and rigidly attached to the cavity created in the tibia. Rigid attachment generally means providing sufficient stability to prevent relative motion between the mount and the tibia during
35 articulation. Such stability may be provided through mere placement of the device in the tibial resection. The femoral cutter is designed to reference the tibial resections 50 and 52 when making the femoral resections. In one embodiment, illustrated in

- 5 Figure 13, the mount is a cradle 62 and is set in the resected tibia. Cutting elements 64 are mounted in the cradle 62 and a flexible shaft 66 connects the cutting element to the motor 68 of Figure 14. The device fits into the resections 50 and 52 in the medial and lateral tibial plateaus. Thus, a cutting element is rigidly held against the femoral condyle and the guide surface of the device sets the depth of resection.
- 10 Optionally, a second cutting element may be placed in the opposite tibial resection. Thus, for example, two cutting elements may be placed in the prepared tibial plateau, one in the medial cavity and one in the lateral cavity, and may be used to simultaneously resect the femoral condyles. In using two cutting elements simultaneously, the cutting elements may be linked together by a hinge mechanism
- 15 65 to further maintain the cutting elements in a common plane while preparing the femoral condyles (Reference is made to Figures 32 and 33).

Thus, for example, in knee surgery, the tool may be mounted to the tibia with the sculpting surface of the tool in engagement with a condylar surface of the femur, that is, one or both of the condyles. As the knee joint is articulated (flexed), the

20 sculpting tool appropriately sculpts the articular surface of the femur in a manner that is dependent upon the individual physiology of that patient's knee, that is, upon the collateral ligaments, the patellar tendon, etc. Although the invention is described in the context of a total knee replacement, it is understood that the invention has application throughout orthopedics where the surfaces of an articulating joint are to

25 be modified or resurfaced to restore function and relieve pain including but not limited to unicondylar knee replacement or allograft joint surface replacement.

In a preferred embodiment, the knee joint capsule is surgically accessed without lateral dislocation of the patella, thereby permitting normal flexion of the knee during the sculpting process. The patient's individual physiology and the interplay

30 between the patient's soft tissues and bone work to guide the device used for sculpting cartilage and bone from the end of the femur and/or tibia as they relate to the knee. In the example of the knee, the tibia travels around the end of the femur along a guided path that is controlled by the ligaments and soft tissues that surround and provide support to the knee.

35 An alternate mount configuration involves an external fixture having burrs attached thereto. The external fixture may be of any configuration that supports the burrs in a position relative to the tibia for sculpting the femur. One example includes

- 5 an external support member having an arm extending therefrom, the burr attached at the distal end of the arm.

The bone-sculpting tool may be powered by a driving mechanism, for example, a motor. The motor may be an electric motor, a pneumatic motor, or a hydraulic motor integral with the cutting element. Note that in the case of a hydraulic motor, a flexible shaft is not necessary. The cutting element may be driven by available surgical power instruments, such as surgical drills, Midas Rex and Anspaqui speed drill/cutters, etc. Such equipment is available in pneumatic and battery operated forms. The cutting element may alternately be driven by a power source developed uniquely for this invention. For example, the power source may be an electric or pneumatic motor. It may also be a hydraulic motor driven by sterile saline solution.

In the case of a hydraulic motor driven with saline solution, the motor may be incorporated into the milling cutter, as illustrated in Figures 15 through 18. The vanes of the hydraulic motor are optionally machined as part of the axel of the milling burr element, or machined into the end face of the milling burr element. Preferably, the housing 53 of the cutting device 55 includes a channel 57 for accommodating saline solution to drive the hydraulic motor. Figures 15 and 16 show an embodiment wherein the vanes of the hydraulic motor are incorporated into the wheel 59 at the distal end of the housing 53. It is also possible, as seen in Figures 17 and 18, to have the blades 61 of the cutting element 55 function as the vanes of the hydraulic motor in which case the saline solution is directed against the cutting element to force rotation.

Figures 19 through 30 depict cross-sectional views of various cutting elements that may be used with the present invention. Figures 19 and 20 show an end and side view, respectively, of one embodiment of a cutting element. Milling burrs 72 are placed in the mount 73 and orientated with the axels in a medial to lateral direction. In Figure 31, multiple milling burrs are shown to provide contact with the femoral condyle as the knee is flexed and the tibiofemoral contact point moves distally. Alternately, one milling burr may be placed in a position such that it remains in contact with the femoral condyle throughout knee flexion. Although only the options of one or four milling burrs are depicted, the invention may be practiced with one or more milling burrs supported in the cradle. Further, the cradle may be

- 5 provided with shoulders 71 having skidding surfaces for contacting the femoral condyle.

Figures 21 and 22 show an end view and a side view, respectively, of an alternate embodiment for a cutting element in which the milling burr 74 is contoured to provide a contoured resection in the femoral condyle. A contoured resection
10 removes less bone and the bone remaining is generally stronger than bone deeper in the condyle.

In another embodiment as shown in Figures 23 and 24, the milling burr 72 is oriented with its axel in an anterior to posterior direction. At knee extension, the tibiofemoral contact point is near the anterior end of the milling burr. As the knee is
15 flexed, the contact point moves posteriorly and approaches the posterior end of the milling cutter.

In similar fashion, Figures 25 and 26 show three milling burrs 76, 77, and 78 in parallel with axels orientated in an anterior to posterior direction. Such an embodiment provides for a broad resection of the femoral condyle in one pass or
20 flexion of the tibia. The medial and lateral milling burrs 76 and 78 may be of smaller diameter than the central milling burr 77, as seen in Figure 27, to provide a smaller corresponding radius between the sidewalls of the cavity created in the femoral condyle and the floor of the cavity.

Cartilage and bone of the femoral condyles may be removed in one or more
25 passes of a shaving element 80 as shown in Figures 28 through 30. The shaving element 80 is off set from the surface of the mount 81 so that a pre-determined amount of bone is shaved off of the femoral condyle with each pass or flexion of the tibia. One or more shaving elements may be supported in the base of the cutting element.

30 Using the instrumentation shown, the articular surface of the femur may be sculpted according to the patient's individual physiology by articulating the tibia with reference to the femur. The method involves providing the apparatus having a bone sculpting tool attached to a bone mount, attaching the mount rigidly to the second bone with the tool in bone sculpting engagement with the articular surface of the first
35 bone, and then sculpting the articular surface by articulating one of the bones with respect to the other. Figure 31 illustrates the kinematics of the articulation of the

5 tibia 16 about the femur 10. The bony resections of the medial and lateral femoral condyles are made by securing the cutter to the tibia and articulating the tibia. The movement of the tibia in reference to the femur follows a J-curve because of the four bar linkage of the anterior and posterior cruciate ligaments, when both are intact. In the absence of one or both cruciate ligaments, the movement of the tibia as the knee
10 is flexed is controlled by the collateral and capsular ligaments. The bony support surface thus created in the medial and/or lateral femoral condyles will be shaped and positioned relative to the kinematics of the given patient.

Preoperative evaluation of patient x-rays may be used to assess deformity of the joint and appropriate spacing required to realign the joint. Additionally, spacers,
15 for example balloons, may be used preoperatively to assess the range of motion of the joint and patient kinematics.

During the surgery appropriate spacers are placed between the bone structures to provide appropriate distraction and alignment of the joint. A distraction force provided between the femur and the tibia during the sculpting procedure may
20 be used to account for material that has worn away from the articular surfaces. Use of a distraction force generally re-establishes normal alignment of the joint. Such spacers also tension the soft tissue structures to reduce the envelop of motion between the bone structures and increase transverse and rotational stability of the joint. The spacer may further be used to support the bone-cutting element during
25 resection of the bone structures. Ligament releases necessary to restore appropriate limb alignment and ligament tension/balance may be performed prior to inserting the spacers.

Any one of a variety of devices may be used to maintain appropriate tension of the ligaments capsule and tendons. Such tensioning devices may include, but are
30 not be limited to, gravity with the weight of the lower limb, intra-articular spacers, bladders, balloons, bellows, gear mechanisms, scissor mechanisms, other expandable devices or other elements that might engage or attach to the opposing sides of the joint. Moreover, the distraction force may be provided by an expanding base in the cutting element. A distraction device may also be useful in conjunction
35 with a mount having skid surfaces on the shoulders. The shoulder allows the depth and shape of the femoral resection to be controlled both by the articulation of the tibia relative to the femur and the shape of the femur.

5 Specifically, for pre-operative assessment, spacers such as balloons may be provided in both the medial and the lateral resections. During surgery, a balloon may be provided in the medial resection and a spacer, for example a bellows, having a cutter attached may be provided in the lateral resection. Alternately a bellows having a cutter attached may be provided in both the lateral and the medial
10 resections.

 Figures 32 and 33 provide closed and open depictions, respectively, of two cutting elements 61 and 63 linked by a hinge mechanism 65 to maintain the cutting elements in a common plane while preparing the femoral condyles. The hinge mechanism 65 allows adjustability of the placement of the two cutting elements 61
15 and 63 in reference to one another.

 After the creation of resections in the tibial plateau, the femoral sculpting tool of Figure 34 may be placed into the recesses in the tibial plateau. The hinge mechanism 65 enables adjustment of the tool arms 172 and 174 in the medial to lateral direction to accommodate the spacing of the tibial plateau resections and
20 holds the tool arms 172 and 174 in a common plane to ensure proper orientation of the femoral condyle resections with respect to one another. Cutting elements 180 are mounted into the tool arms 172 and 174 and are driven by a driving mechanism, for example, a pair of gear mechanisms. In a preferred embodiment, the gear mechanisms are driven by a common flexible drive cable 178 that drives a gear box
25 providing torque to secondary drive cables 184 and 186. As shown in Figure 35, the surfaces of the cutting elements 182 are roughened, or have cutting flutes, to provide cutting of the femoral condyles.

 As shown in Figure 36, the knee femoral sculpting tool may be placed in the resections made in the tibial plateau 190. The cutting discs 180 are in contact with
30 the femoral condyles 188. The knee is flexed resulting in relative motion of the femoral condyles across the cutting discs, thereby resecting the medial and lateral condyles of the femur at the same time. Soft tissue structures spanning the knee guide the cutting motion along the normal kinematic motion of the given knee joint. The cutting discs 180 rotate in a transverse plane.

35 Figures 37 and 38 provide end and top views, respectively, of a cutting element 100 supported in a platform 102 that is configured for elevation via fluid

5 pressure applied to a distractor 104 that surrounds the cutting element 100. Applying pressure to the distractor 104 forces the milling burr into the femoral condyle to a predetermined depth as set by the top surface of the cutting element. The distractor 104, in combination with the top surface of the cutting element, ensures proper resection depth while tensioning the soft tissue structures spanning
10 the knee joint. The benefit of tensioning the soft tissue structures is to reduce the envelop of motion of the knee, stabilize the knee and provide increased accuracy and repeatability of the femoral condyle resections. An alternate embodiment may use a spacer placed between the floor of the cavity created in the tibia and the bottom of the cutting element to provide a distraction force.

15 Figure 39 shows balloon spacers 110 used to support the femoral condyles to distract the femur 10. Syringes or pumps 112 may be attached via hoses 114 to balloon spacers 110. Balloon spacers 110 are an example of an expandable spacer. Where an expandable spacer is used, pre-operative evaluation should be performed. During surgery an expandable spacer is placed between the bone structures to be
20 resected. The cutting element may be housed in the dynamic spacer with the cutting element adjustable to the dynamic spacer to set the depth of resection. The dynamic spacer may function under load control in which case a constant distraction force is applied between the bone structures throughout a range of motion, or under displacement control. Under displacement control, a constant displacement is
25 maintained between the bone structures throughout a range of motion. In each case, the dynamic spacer houses the cutting element and the cutting element is held at a pre-set depth relative to the bone structure being resected while the joint is flexed and extended. The dynamic spacer allows the kinematics of the joint to define the resection path in each of the bone structures.

30 As the tibia is articulated through flexion and extension, the femoral cutter prepares resections in the femoral condyles for receiving femoral components of a knee implant. Figure 40 shows the bone resections 130 and 132 in the femoral condyles. Figures 41 and 42 depict alternate embodiments of the bone resections in the femoral condyle as may be desired.

35 **Implants.** The surgical procedure is preferably performed through minimally invasive incisions that do not necessitate subluxation or dislocation of the patella. Therefore, implants such as the femoral, tibial or patellar implants are designed that

- 5 may be fit through minimally invasive incisions and either oriented or joined within the joint. The femoral and tibial implants may be attached to bone with conventional bonding methods such as, but not limited to, polymethylmethacrylate, or by direct attachment to bone as with, but not limited to, a porous ingrowth surface.

The tibial baseplate is optionally configured as one piece to cover most of the prepared surface of the tibial plateau as relates to the knee. If configured as a single platform, the tibial baseplate provides a capture mechanism for a fixed bearing or a mobile bearing insert for either the medial or lateral tibiofemoral compartment. As an option, a single platform is designed that provides a fixed bearing capture mechanism for the medial tibiofemoral compartment and a mobile bearing capture mechanism or a simple platform to receive a mobile bearing insert for the lateral tibiofemoral compartment. Since right and left tibial baseplates are required, the same baseplate may be used for a mobile bearing medial insert and a fixed bearing lateral insert.

Alternatively, as depicted in Figure 43, the tibial implants may be configured as separate plateau baseplates for the medial and lateral compartments. These platforms might be oriented one to the other by an alignment instrument that dictates their orientation in relationship to each other and/or to the femoral components. The tibial baseplates may be fixed bearing and manufactured completely of polyethylene. Thus, fixed bearing tibial components 150 with a metal support tray 151, and mobile bearing tibial components 152 with a metal support tray 153 may be used in the same knee replacement surgery. Furthermore, the tibial baseplate may accommodate separate fixed and mobile bearing inserts in either or both medial and lateral compartments.

It is preferable to place all of the implants through small incisions. As seen in Figure 44, the femoral implants include a first component 132 to resurface the articulating surface of the medial condyle and a second component 130 to resurface the articulating surface of the lateral condyle. An optional third component 134 may be provided to resurface the femoral side of the patellofemoral joint. The convex surface of the femoral condyle is the bearing surface and interacts with the tibial bearing implants. Optionally, the femoral component(s) may include a fin along its support or convex internal surface for upward driven implantation. The fin may be shaped as a web extending from one portion of the internal surface to another.

5 As shown in Figure 42, the lateral femoral implant may be continuous with the patellar flange forming a unitary piece 136 that may be passed through a small incision. To accommodate the continuous piece, the lateral condylar component and the patellofemoral component optionally may be a single component 136 extending from the top of the patellofemoral groove and extending over the lateral condyle both
10 distally and posteriorly, as seen in Figure 45. Figure 45 provides a side view of a femoral implant combining the lateral condylar component and the patellofemoral component into a single component 136.

 The bearing elements may be manufactured of ultra high molecular weight polyethylene but may also be manufactured of any suitable biocompatible material
15 as known in the art. The bearing elements generally include three compartments: medial tibial condyle, lateral tibial condyle and patella. Preferably, a choice of bearing elements is provided for either fixed or mobile bearing of each compartment. Thus, for example, the surgeon would have at his discretion inserting either a mobile bearing or a fixed bearing insert into each of the tibial components, one medial and
20 one lateral.

 The femoral components may include an alignment device to orient separate femoral components in relationship to one another and/or to the tibial components. Surgical navigation may be used in concert with bone preparation and component orientation.

25 The femoral components are provided in a variety of sizes and optionally include components that are flexible to provide optimum fit for minor variations in the shape of the prepared femoral condyles.

 Figure 46 is an illustration of an optional embodiment of the femoral condyle implants configured as flexible implants. The outer surface of the femoral condyle
30 implant is a thin sheet of metal forming an articular surface, preferably of cobalt chromium alloy. Other suitable implant grade alloys, polymers, or metals, for example, stainless steel, titanium alloy, or Nitinol, may be used. In order to provide uniform deflection in one plane, the implant is thin and of uniform cross section. The support surface of the femoral condyle implant is lined with molded bone cement,
35 such as polymethylmethacrylate (PMMA or PMA), and spacers that are bonded to the articular surface. The spacers may be shaped as blocks or any other

5 configuration suitable for molding in place during fabrication. Generally, the spacers are shaped to span the femoral condyle implant from side to side, in a coronal plane, while providing spaces between spacers at given intervals to facilitate mild flexing of the articular surface. Such flexing enables the flexible femoral condyle implant to conform to the unique shape of the prepared bony support surface in the femoral
10 condyle, thereby taking full advantage of the kinematically defined support surface. Such implants are provided in a range of sizes to accommodate individual patient physiology and to minimize the amount of flexing a given implant may make in conforming to the prepared surface. Hence, the distortion of the articular surface is minimal.

15 In use, the resected femoral condyle is covered with doughy bone cement. The femoral implant is placed and loaded against the resected femoral condyle until the bone cement cures.

The preferred method for preparing the femoral condyle uses the tibia as a support for the milling cutter. The soft tissue structures of the knee provide the path
20 of motion to move the cutter through the femoral condyle. The kinematics of the knee are well understood and defined. This approach necessarily results in a unique shape machined into each femoral condyle due to variations in soft tissue structures and bony structures from patient to patient.

In an alternate embodiment, the femoral condyles may be ridged and of given
25 size. Each implant is composed of a plurality of components 170. The components 170 are cemented in place with bone cement, which acts as a grouting material to fill the space between the implant and the supporting bone. Bone cement has been shown to provide long term implant stability when applied in thicknesses up to two millimeters. Hence, a range of implant sizes covers the range of femoral condyle
30 sizes anticipated and the variation in shape anticipated.

While a preferred embodiment of the present invention has been described, it should be understood that various changes, adaptations and modifications may be made therein without departing from the spirit of the invention and the scope of the appended claims.

35 **Hip Joint Anatomy and Surgical Approaches.** Figure 47 illustrates the general anatomy of the hip joint and a typical surgical approach 200 to the hip joint to

5 expose the proximal femur 202 and the acetabulum 204. In traditional total hip replacement there are generally four surgical approaches to the hip joint. These include posterior approaches without trochanteric osteotomy, trans-trochanteric approaches, anterior approaches without trochanteric osteotomy, and Smith-Peterson approaches. Such approaches are described in detail in various
10 orthopedic reference texts such as "Operative Orthopedics," edited by M. W. Chapman, MD, J.B. Lippincott Company, 1988. In addition, a direct lateral approach is commonly used for total hip arthroplasty. The most common surgical approach to the hip is posterior, and the musculature disrupted may include the short internal and external rotators, tensor fascia femoris, quadratus femoris, piriformis, and on
15 occasion part of the gluteus medius and minimus, and the gluteus maximus.

In minimally invasive total hip surgery, the incision 206 is typically 6 cm as shown in Figure 48. While 6 cm, or 2-4 inches, is a typical length for a minimally invasive surgical incision, there may be some variation due to patient physiology, surgeon preferences, and/or other factors. The surgical approach involves
20 separating the gluteus maximus muscle through blunt dissection to gain access to the hip joint capsule and the trochanteric fossa. Muscle disruption is usually limited to release of the piriformis tendon at the trochanteric fossa. It should be noted that there are variations to the surgical approaches described that are known to someone skilled in the art.

25 Figure 48 illustrates a minimally invasive surgical approach to the hip joint. The general approach is posterior, and the musculature disrupted includes release of the piriformis tendon. The incision is just large enough to expose the femoral head and acetabulum, and to enable placement of a hemispherical reamer 208, drive mechanism 210, and femoral broach 212.

30 In contrast to the minimally invasive technique provided, a total hip replacement surgery involves exposing the hip joint through a large incision to provide the surgeon full visualization of the hip joint and the acetabular region and access for surgical power instruments. The femoral head is removed and the femoral canal is reamed and broached to prepare the bony surface to support the hip
35 stem. The stem may be cemented in place or press fit for bony ingrowth. The acetabulum is prepared, most typically using a hemispherical reamer attached to a surgical hand drill to remove cartilage down to bleeding bone. The surgical exposure

- 5 as shown in Figure 52 generally ranges between eight and twelve inches in length and may result in extensive trauma to the soft tissues surrounding the hip joint.

Minimally Invasive Acetabular Reamer System(MIAR). As seen in Figure 49, the MIAR of the present invention, for use with hip replacement surgery, is either a modular or non-modular construct comprising a femoral trial 216, a drive mechanism 218 (either integral or separate) and a hemispherical reamer 220 or similar device for removing cartilage and bone from the acetabular fossa. The hemispherical reamer 220 or similar device includes an attachment component (not shown) for attaching either to the femur, directly or indirectly, or to a mount that itself is attachable to the femur, directly or indirectly. Discussion of the attachment of the MIAR to the femur, directly or indirectly, should be read as broadly encompassing attachment by the reamer directly to the femur (or femoral component) or attachment by the reamer to a mount that is attached to the femur (or femoral component). The reaming system, especially as a modular construct, enables placement of the components through a small incision and minimizes the number of components in the instrument set. In the minimally invasive procedure, the proximal femur does not have to be displaced during acetabular preparation as is necessary with conventional hip arthroplasty. Therefore, the procedure requires only a minimal release of muscles and tendons and, consequently, minimal trauma to muscles and tendons that attach to the proximal femur. Although the invention is described in the context of a total hip replacement, it is understood that the invention has application throughout orthopedics where the surfaces of an articulating joint are to be modified or resurfaced to restore function and relieve pain. The MIAR system uses a drive mechanism anchored to or mounted on a device such as a reamer, broach, or other suitable device that is secured to one bone and, with the joint reduced or placed in position of reduction, may be activated to prepare, with a hemispherical reamer or suitable bone sculpting tool, the opposite side of the joint to receive artificial components.

With reference to the hip joint, the femoral head is removed either before or after the femoral canal is reamed and broached to prepare a bony surface to support the hip stem or broach to be inserted. The minimally invasive acetabular reamer is mounted to the broach, reamer, trial femoral component or other device inserted into the proximal femur. It is possible to attach the MIAR directly to the proximal femur,

5 however the instruments and the femoral implant provide an advantageous support structure as these instruments, such as rasps, broaches, trials or the implant, conform closely to the prepared bony surface and provides a rigid metal structure to which the MIAR may be mounted. Therefore, in the preferred embodiment, the MIAR is directly or indirectly attached to the femoral broach that is secured within the
10 proximal femoral canal. It is noted that throughout the description, rasps, trials, broaches, implants and stems are used interchangeably in relation to the MIAR system. Additional embodiments include attachment of the MIAR directly to the femur, the femoral trial or the femoral implant. With the MIAR directly or indirectly attached to the femur, the reamer head is placed into the acetabulum. The MIAR is
15 activated to initiate cartilage and bone removal as the femur is positioned. The operating surgeon controls the MIAR by placing and/or moving the leg as necessary to create a spherical reaming of the acetabulum. Surgical navigation may be utilized.

The femoral trials are available in an array of sizes to accommodate the size
20 range of the proximal femur. The hemispherical reamers are available in a range of diameters to accommodate the size range of the acetabulum. In the preferred embodiment, the drive mechanism is interchangeable amongst the femoral trials and amongst the hemispherical reamers. An alternate embodiment includes a drive mechanism for each femoral trial or groups of trials. The trials may be grouped by
25 size, or by right and left. The example given is for the MIAR attached directly or indirectly to a femoral rasp. Similar combinations are possible when the drive mechanism is directly or indirectly attached to a femoral trial or femoral implant.

An example of a procedure according to the present invention includes the following steps: the appropriate femoral trial is placed into the prepared proximal
30 femur; the drive mechanism is placed onto the proximal aspect of the femoral trial followed by placement of the appropriate sized hemispherical reamer onto the drive mechanism; the hip is reduced and the reaming system is activated to prepare the acetabulum. Of course, if the MIAR is not modular, it is placed as a unit, the hip is reduced, and the reaming system is activated.

35 As shown in Figure 54, the acetabular reamer 220, which is provided in a range of sizes, attaches to the drive mechanism 218 at the support plate 235, which provides quick attachment to the drive mechanism 218. The reamer is preferably

5 rigidly supported on the femoral side such that sufficient stability is provided to prevent relative motion between the MIAR and the femur during articulation. Such stability is generally provided through the placement of the broach 216, femoral trial or femoral implant in the femoral canal. Figure 49 illustrates an embodiment of a MIAR in accordance with the present invention.

10 Support for the MIAR is provided by a femoral broach 216. The drive mechanism 218 is supported by the femoral broach 216. Figure 49 further shows the drive shaft 240 of the drive mechanism 218 supported in the drive mechanism housing, which is supported by the femoral broach 3216.

As shown in Figure 51, the drive mechanism 218 may use a worm 238 and
15 worm gear 236 combination, bevel gears, spur gears, belts or chain drives or other suitable mechanism to transfer rotation or oscillation to the acetabular reamer. In Figure 50, a worm gear 236 is attached to the drive shaft 234 which in turn is driven by a worm (behind the worm gear). A worm and worm gear combination represents only one possible drive mechanism that may be used to drive the acetabular reamer
20 and is intended to be illustrative but not limiting. Any other drive mechanism known to those skilled in the art may be used with the present invention. Figure 51 depicts the worm 238 supported by an input drive shaft 240.

As shown in Figure 53, a flexible drive cable 228 is attached to the drive shaft 240. Optionally, a sleeve mounted to the drive mechanism housing may extend
25 through the surgical incision and contain the drive shaft 240 with the flexible cable 221 attached outside of the surgical incision. Torque generated by the drive mechanism is reacted between the drive mechanism and the femoral trial by a rotational stop 242. (See Figure 8.)

The acetabulum is prepared by rotating or oscillating a hemispherical reamer
30 within the acetabulum. The hemispherical acetabular reamers may be reamers, cutters, or other devices used for removing cartilage and bone from the acetabular fossa. Alternatively, non-mechanical cutting instruments such as lasers, water jet cutting, ultrasonic probes, chemical or other devices to remove tissue can be used. In the current invention, such devices involve rotation or oscillation of the reamer
35 with the device supported by the femur. As shown in figure 52, the MIAR may be self-contained with an internal power source to drive the reamer, or may have an

5 external power source to drive the reamer. Likewise, the motor 222 may be internal to the drive mechanism or may be external with torque transferred to the drive mechanism via appropriate shaft or connection. The drive mechanism may be constructed of mechanical components such as gears, cams, levers, belt and pulleys or chains. Power sources for the drive mechanism to drive the reamer include fluid
10 to drive a hydraulic motor, gas to drive a pneumatic motor, electrical to drive an electric motor (either integral to the femoral trial or via flexible drive cable connecting the motor to the drive mechanism), solenoid or other suitable power source to provide rotation or oscillation to the reamer. Alternately, the drive mechanism may be driven by available surgical power instruments, such as surgical drills, Midas Rex and Anspaq hi speed drill/cutters, etc. Such equipment is available in pneumatic and
15 battery-operated forms. In a preferred embodiment, the drive mechanism is driven by an external power source transferring torque through a flexible drive shaft. Alternatively, the power source may be housed within the femoral trial or broach.

Alternately, the drive mechanism may be configured for use with any one of
20 the attachment mechanisms provided by various manufacturers of total hip systems to attach trial necks to femoral trials. The attachment thus may be a peg in groove, a peg in hole, a conical taper, a screw fit, or a threaded attachment. In a preferred embodiment, the drive mechanism is designed to attach to a femoral trial or rasp/trial provided with the total hip system with which the MIAR is being used. The proximal
25 surface of the drive mechanism is designed with a quick attach mechanism that fits an array of acetabular reamer sizes.

In another embodiment the drive mechanism is supported by the femoral taper that supports the femoral head implant or implant trial. The femoral stem trial is placed into the prepared femoral canal and the appropriate femoral neck trial is
30 placed onto the stem trial. The drive mechanism is placed onto the femoral neck trial taper and the appropriately sized acetabular reamer is directly or indirectly attached to the drive mechanism. Optionally, the femoral stem trial and femoral neck trial may be integrally formed. In this approach, the femoral canal is prepared and the appropriately sized femoral stem is selected based on the patient's femoral anatomy.
35 The femoral stem implant is placed into the prepared femur and the drive mechanism with appropriately sized acetabular reamer is placed onto the implant to prepare the acetabulum.

5 In alternate embodiments, the drive mechanism may be integral to the femoral trial or the acetabular reamers. The hemispherical reamers are modular and allow changing reamer sizes during the procedure. As seen in Figure 52, in surgical use, the appropriate femoral broach 216 with integral drive mechanism, in this case a hydraulic motor 222, is placed into the prepared proximal femur and the
10 appropriately sized hemispherical reamer 220 is directly or indirectly attached to the broach via the drive mechanism. The trial stem includes a drive mechanism 222 that is housed within the proximal aspect of the broach 216. The drive mechanism 222, which may be a hydraulic motor within the broach, rotates the drive shaft 226 and support plate 235 which in turn rotate the acetabular reamer 220 to prepare the
15 acetabulum. Alternatively, as seen in Figure 58, the appropriate acetabular reamer 220 with integral drive mechanism 218 is placed into the acetabular fossa 232 and directly or indirectly attached to the femoral trial 216. Acetabular preparation is performed with the hip joint articulated (reduced).

Figures 49, 50, 51, 53 and 54 illustrate the mechanical drive mechanism used
20 in one embodiment of the MIAR system. Figure 53 shows the MIAR placed into the proximal femur 230 with the hemispherical reamer 220 in contact with the acetabulum 232. Figure 54 illustrates an exploded view of one embodiment of the MIAR system. The drive shaft 234 extending distally from the drive mechanism 222 passes into receiving hole 254 to attach the drive mechanism 222 to the broach 216.
25 The anti-rotation pin 242 engages the receiving hole 256 to add stability and rotational resistance between the drive mechanism and broach. The reamer 220 attaches to a support plate 235 that is part of the drive mechanism 218. The surface 258 of the reamer 220 conically locks to the support plate 235.

In yet another embodiment the acetabular reamer is assembled in a collapsed
30 state to allow ease of reduction of the hip joint with the MIAR system in place. The acetabular reamer is elongated from the femoral housing or from the drive or gear mechanism of the MIAR. This elongation may be accomplished by a variety of devices, for example shim plates, spacers or other suitable device placed between the elements. Alternatively the MIAR may be elongated by means of pneumatic
35 pressure, lead screws or other power sources. The manner by which the MIAR is elongated is not critical to the invention and any suitable device or method may be used. When sufficient resistance is encountered by the joint capsule and/or other

5 soft tissue elements about the hip, the MIAR is activated to initiate acetabular bone preparation. The process of acetabular reaming is enhanced by pressure created through tensioning the soft tissue elements. In the example of using pneumatic force, gas pressure first elongates the MIAR construct. After a specified amount of resistance is encountered to elongation, pneumatic pressure is transferred to
10 elements that generate torque to turn the acetabular reamer.

Minimally Invasive Acetabular Impaction System. Once the acetabulum has been prepared, an acetabular implant is secured to the supporting bone, usually by either bone cement or press-fit. In the case of a cemented acetabular component, the bone surface is oversized relative to the implant size. The bony
15 surface and the implant are covered with bone cement. The implant is then placed into the acetabulum and pressed into position forming a uniform layer of bone cement between the acetabular component and supporting bone. In the case of a press fit acetabular component, the bone surface is line-to-line or slightly undersized relative to the implant size. The implant is impacted into place in the supporting
20 bone. In standard total hip surgery, a straight handled impactor is commonly used to impact the acetabular component. The extensive exposure typically used in traditional total hip surgery provides the clearance to align the impactor relative to the acetabulum. However, in the case of a minimally invasive total hip replacement, the incision is too small to allow proper orientation of a standard straight handled
25 impactor. Use of a standard impactor requires making a second incision to pass the impactor through muscle and tissue in the correct orientation relative to the acetabulum. The acetabular component must be positioned properly to provide normal function and to prevent dislocation of the hip joint. Making a second incision and disrupting more muscle is contrary to the goal of a minimally invasive procedure.
30 Therefore, a device that impacts the acetabular component through a minimally invasive incision is needed. In one embodiment, the current invention includes a device designed to directly or indirectly attach to the femoral trial and provide an impaction force to properly seat the implant. A variety of acetabular components and methods for placement thereof may be used. Example components for implanting in
35 the acetabulum include, but are not limited to, cemented shells or press fit cups.

As seen in Figure 56, the impaction device preferably includes a pneumatic impaction hammer 260 mountable to the femoral broach 216 and an optional

5 attachment component for attaching to the shell 252 of the acetabular component. The impaction device 260 and acetabular component 252 may be placed into the surgical site independently and assembled in the operative site. Alternatively, the impaction device 260 and acetabular component 252 may be assembled prior to placing the impaction device onto the broach 216. With the acetabular shell directly
10 or indirectly attached to the impactor and the impactor secured to the femoral broach, the shell is placed into the acetabulum by reducing the hip joint. The broach, femur and mass of the leg serve as counter weights to counteract the force of the impaction device. An additional counter weight may be directly or indirectly attached to the impaction device via a connection shaft extending outside of the incision and
15 attaching to a weight or an external resistance to impaction forces.

The impaction device may be powered by a pneumatic impaction hammer, a hydraulic piston, a linear actuator or solenoid, an electromechanical device, a spring activated device or any other suitable force generating mechanism. The power source may originate outside of the operative site or may be integral with the
20 impaction device. As an alternative, a hand held impactor with a handle angled to allow access through a minimally invasive incision may be used to impact the acetabular component. In a preferred embodiment, the impactor is a single ended air driven piston and cylinder as shown in Figure 67. The back face 292 of the impactor housing 268 is configured to attach to the broach previously described.
25 Within the housing is a primary piston 282 that travels in a primary cylinder 294. In its retracted position (shown) a push rod 286 of a secondary piston 280 engages a retaining groove 288 in a primary piston 282. The secondary piston 280 is held in an extended position by a secondary spring 278. Air pressure is applied via a primary tube 284 to the back of the primary piston 282 to charge the system. The primary
30 piston 282 is held in place by the push rod 286 of the secondary piston 280. Air pressure is applied to the secondary tube 276 to pull the push rod and the secondary piston 280 out of the retaining groove 288 in the primary piston 282, thereby releasing the primary piston 282 to impact the top surface of the cylinder 298. The impaction force is carried through the impactor housing 268 and delivered to the
35 acetabular shell (not shown) via a cup adaptor 264. The cup adaptor 264 has a threaded end 290 that engages the acetabular shell. The other end of the cup

- 5 adaptor 264 has a box shaped recess 300 that fits over a mating prominence 270 on the top surface of the impactor housing 268.

After an impaction cycle, the pressure to the primary tube 284 is released and the primary piston 282 is forced back into a retracted position by a return spring 274. When the primary piston 282 is in its retracted position, the air pressure to the
10 secondary tube 276 is released and the secondary piston 280 is pushed back into locked position by a secondary return spring 278. Pressure is reapplied to the primary tube 284 to charge the impactor and the cycle is repeated.

In surgical use, the cup impactor 260 and broach may be assembled outside of the surgical site, then placed into the prepared proximal femur. Alternatively, the
15 broach may first be placed into the proximal femur, then the cup impactor 260 attached to the broach. With the cup impactor 260 in place, the cup adaptor 264 is attached to the cup implant and the recess 300 in the adapter is placed over the mating prominence 270 on the top of the cup impactor. The hip joint is reduced, placing the acetabular shell into the acetabulum. An alignment guide (not shown) is
20 attached to the cup impactor to aid the surgeon in properly orientating the shell with respect to the pelvis. Alternatively, a surgical navigation system may be used to position the acetabular shell by referencing the cup impactor and the acetabulum. Once in position, the shell is impacted into the acetabulum by triggering the cup impactor with successive impactions. In a preferred embodiment, the trigger
25 releases one impaction, then the cup impactor resets for a further impaction as necessary. In an alternate embodiment, the trigger releases continuous impactions for the duration that the trigger is on.

Of course the impaction device is suitable for use in placing an implant other than an acetabular component. The impaction device may be used for seating an
30 implant in a second bone in any joint replacement wherein the implant may be placed on the impaction device, aligned with a second bone, and force imparted to the implant, the force being reacted with the first bone and the second bone.

A typical surgical procedure for the MIAR is as follows: Using the instrumentation shown, the articular surface of the acetabulum may be sculpted
35 according to the patient's individual physiology by articulating the femur with reference to the acetabulum. The method involves providing an apparatus having a bone sculpting tool directly or indirectly attached to a bone mount such as a femoral

- 5 trial stem, attaching the mount rigidly to the femur with the tool in bone sculpting engagement with the acetabulum, and then sculpting the acetabulum by articulating the femur with respect to the joint.

The hip joint is a ball in socket joint, hence rotation of the femur while supporting the MIAR will result in a spherical preparation of the acetabulum.
10 Alternatively, the MIAR, having a suitable reamer and drive mechanism, may be placed into the acetabulum to remove bone without rotating the femur.

In a preferred embodiment, the trochanteric fossa is surgically accessed with minimal disruption of muscle and tendon insertions to the trochanter and surrounding area. The approach may be at the posterior border of the gluteus medius and
15 minimus, anterior in the interval between the sartorius and the rectus, or a direct lateral exposure. The hip may be dislocated posteriorly if a posterior approach is used or anteriorly if either a lateral or anterior approach is used. Alternatively, the hip may remain reduced while the femoral canal is prepared and the femoral neck is resected.

20 The femoral neck is resected and the femoral head is removed. The resection and removal may be performed with conventional cutting devices such as oscillating saws. The femur is oriented to align the femoral canal with the incision. The femoral canal is prepared using sequential reaming and broaching. Bony preparation is per the technique specified for the particular total hip stem being used
25 and at the surgeon's discretion.

An appropriately sized femoral trial is placed into the femur. The drive mechanism is directly or indirectly attached to the femoral trial. Preferably, the drive mechanism is designed to mount directly onto the femoral trial.

The acetabular reamer is directly or indirectly attached to the drive
30 mechanism. The appropriate acetabular reamer is selected by the surgeon. The surgeon may choose to measure the diameter of the removed femoral head as an aid in selecting the most appropriately sized acetabular reamer. The surgeon may choose to use surgical navigation.

The hip joint is reduced and the hip is articulated with the drive mechanism
35 and acetabular reamer in place. Elongation of the MIAR construct is optionally carried out to appropriately tension the soft tissue elements about the hip. The drive

5 mechanism is activated to prepare the acetabulum. If necessary, the femur may be advanced while the hip joint is manipulated to ensure spherical and uniform reaming of the acetabulum. Imaging may be used to check the orientation and depth of the acetabular reamer.

10 At the surgeon's discretion, the depth and uniformity of reaming may be checked periodically during the procedure. This may be done by dislocating the hip, removing the reamer and attaching the illumination and irrigation devices (or a combined illumination and irrigation device) to the femoral trial. The hip is reduced with the illumination and irrigating devices in place and the operative site is cleared with irrigation and suction. The prepared surface of the acetabulum may then be
15 inspected. After inspection, the illumination and irrigation devices are removed and the drive mechanism and reamer are replaced. Alternatively, the depth of reaming may be assessed under fluoroscopic imaging of the hip joint.

The articulation of the hip joint to prepare the acetabulum may be repeated with sequentially larger reamers until the appropriate size is reached. Further, the
20 size and preparation may be checked with the illumination and irrigation devices as necessary. Once the appropriate size is reached, the acetabular reamer and the drive mechanism are removed.

After preparation of the acetabulum, an appropriate acetabular component is implanted. The appropriate acetabular component may be pre-selected or may be
25 selected after surgical preparation of the acetabulum. If the desired component is a cemented cup, the cup is cemented in place.

If the desired component is a press fit cup, a cup impactor is attached to the broach and placed into the prepared proximal femur. Alternatively, the broach may be placed in the prepared femoral canal first and then the cup impactor attached to
30 the broach. The acetabular shell is attached to the cup adaptor and placed onto cup impactor. The hip joint is reduced and the shell is positioned in the acetabular fossa. An alignment guide is attached to the cup impactor to aid the surgeon in proper orientation of the shell during impaction. The cup impactor is triggered, thereby impacting the shell. An alternative technique for placing a press fit cup may use
35 image guided surgery or an alignment device protruding from the incision. The guiding system is used to advance the cup into proper orientation. The minimally

- 5 invasive acetabular impactor (MAI) is activated to securely seat the cup into the acetabulum. Regardless of technique, after placement of the press fit cup, the impaction device is removed. Alternatively, a surgical navigation system may be used for positioning, aligning, and monitoring the cup or cup impactor during impaction. Cup monitoring includes real time evaluation of the cup position relative
- 10 to anatomical landmarks captured by the surgical navigation system after preparing the acetabulum and before placing the cup so as to indicate cup seating and cup alignment.

- The acetabular liner is placed into the shell and a trial femoral neck and head are placed onto the femoral trial. The range of motion and hip stability are checked
- 15 and the appropriate femoral implant is selected. The femoral trials are removed and the femoral component is implanted per manufacturer specifications.

- Accordingly, an apparatus and method for minimally invasively sculpting the articular surface of a first bone that normally articulates with a second bone is provided. In one embodiment, a bone sculpting tool is provided on the tibia for
- 20 sculpting the femur when the tibia is articulated with reference to the femur. In another embodiment, the acetabulum is sculpted by providing a bone sculpting tool on the femur, aligning the bone sculpting tool with the femur and engaging the surface of the acetabulum with the bone sculpting tool.

- Additional components or steps as known to those skilled in the art may be
- 25 performed within the scope of the invention. Further, one or more of the listed steps or components need not be performed in a procedure within the scope of the present invention.

5 CLAIMS

1. An apparatus for sculpting the articular surface of a first bone that normally articulates with a second bone, the apparatus comprising:
 a bone-sculpting tool including an attachment portion for attaching the
10 bone-sculpting tool to the second bone in a position for sculpting the articular surface of the first bone.
2. The apparatus of claim 1, further comprising a mount configured for attachment to the attachment portion of the bone-sculpting tool, the mount being attachable to the first bone to mount the tool in position to sculpt the
15 articular surface of the first bone.
3. The apparatus of claim 2, wherein the mount is configured for rigid attachment to the second bone.
4. The apparatus of claim 2, wherein the mount is integral to the bone-sculpting tool.
- 20 5. The apparatus of claim 2, wherein the mount is an external fixture.
6. The apparatus of claim 1 or 2, wherein the first bone is a femur and the second bone is a tibia, the bone-sculpting tool being configured for attachment to the tibia in a position for sculpting the articular surface of the femur.
- 25 7. The apparatus of claim 1 or 2, wherein the first bone is an acetabulum and the second bone is a femur, the bone-sculpting tool being configured for attachment to the femur in a position for sculpting the articular surface of the acetabulum.
8. The apparatus of claim 1 or 2, wherein the attachment portion of the bone-sculpting tool is adapted for direct attachment to the second bone.
30 9. The apparatus of claim 1 or 2, wherein the attachment portion of the bone-sculpting tool is adapted for indirect attachment to the second bone.
10. The apparatus of claim 9, wherein the second bone is the femur and the attachment portion of the bone-sculpting tool is adapted for attachment to a
35 femoral broach.
11. The apparatus of claim 9, wherein the second bone is the femur and the attachment portion of the bone-sculpting tool is adapted for attachment to a femoral stem.

- 5 12. The apparatus of claim 1 or 2, wherein:
 the bone-sculpting tool includes a bone-sculpting surface generally
 symmetrical about an axis of rotation of the tool, and wherein
 the bone-sculpting tool is positioned with respect to the articular
 surface of the first bone with the axis of rotation generally parallel to an
10 articular plane defined by normal articulation of one of the bones with respect
 to the other.
13. The apparatus of claim 12, wherein:
 the bone-sculpting surface includes one or more milling burrs wherein
 the milling burr or burrs have an axis of rotation generally oriented in an
15 anterior to posterior direction.
14. The apparatus of claim 12, wherein the bone-sculpting surface is generally
 cylindrical in shape.
15. The apparatus of claim 1 or 2, wherein:
 the bone-sculpting tool includes a bone-sculpting surface generally
20 symmetrical about an axis of rotation of the tool, and wherein
 the bone-sculpting tool is positioned with respect to the articular
 surface of the first bone with said axis of rotation generally perpendicular to an
 articular plane defined by normal articulation of one of the bones with respect
 to the other.
- 25 16. The apparatus of claim 15, wherein:
 the bone-sculpting surface includes one or more milling burrs wherein
 the milling burr or burrs have an axis generally oriented in a medial to lateral
 direction.
17. The apparatus of claim 13 or 16, wherein the one or more milling burrs
30 include an inside burr, an outside burr, and a middle burr, the middle burr
 having a larger radius than the inside and outside burrs.
18. The apparatus of claim 13 or 16, wherein the burr or burrs are contoured to
 provide a cutting surface that is convex to the axis of rotation.
19. The apparatus of claim 15, wherein the bone-sculpting surface is generally
35 cylindrical in shape to produce a sculpted groove having a floor that is curved
 in the plane but that is generally straight in a direction perpendicular to the
 plane.

- 5 20. The apparatus of claim 1, 2 or 7 wherein the bone-sculpting tool is designed for rotation.
21. The apparatus of claim 1, 2, or 7, wherein the bone-sculpting tool is designed for oscillation.
22. The apparatus of claim 1, 2, or 7, wherein the bone-sculpting tool comprises a hemispherical reamer.
- 10 23. The apparatus of claim 1 or 2, further comprising a distractor configured for insertion between the first and second bones for distracting the first bone from the second bone while allowing normal articulation between the first and second bones.
- 15 24. The apparatus of claim 23, wherein the distractor is a fixed thickness spacer.
25. The apparatus of claim 23, wherein the distractor includes one or more surfaces engageable with the respective bones, and means enabling adjustment of the distances between the surfaces.
26. The apparatus of claim 25, wherein the distractor is a fluid filled catheter or balloon.
- 20 27. The apparatus of claim 25, wherein the distractor is a mechanical wedge.
28. The apparatus of claim 1, 2, or 7, wherein the bone-sculpting tool is adapted for elongation.
29. The apparatus of claim 26, wherein the bone-sculpting tool has an axis of rotation, and the elongation is along the axis of rotation.
- 25 30. The apparatus of claim 26, further comprising a lead screw for elongation of the bone-sculpting tool.
31. The apparatus of claim 26, further comprising shims for elongation of the bone-sculpting tool.
- 30 32. The apparatus of claim 26, further comprising a pneumatic powered device for elongation of the bone-sculpting tool.
33. The apparatus of claim 2, wherein the mount further comprises a positioning element for positioning the bone-sculpting tool at variable elevations such that the bone-sculpting tool depth in the first bone during articulation may be adjusted.
- 35 34. The apparatus of claim 33, wherein the mount further includes shoulders having skid-surfaces thereon.

- 5 35. The apparatus of claim 33, wherein the positioning element provides a dynamic distraction between the first bone and the second bone.
36. The apparatus of claim 1, 2, or 7, further comprising a drive mechanism for driving the bone-sculpting tool.
37. The apparatus of claim 36, wherein the drive mechanism is integral to a
10 mount.
38. The apparatus of claim 36, wherein the drive mechanism is configured for attachment to a femoral stem.
39. The apparatus of claim 36, wherein the drive mechanism comprises a gearbox.
- 15 40. The apparatus of claim 36, wherein the drive mechanism comprises a worm and worm gear combination.
41. The apparatus of claim 36, wherein the drive mechanism comprises a bevel gear combination.
42. The apparatus of claim 36, wherein the drive mechanism includes a motor.
- 20 43. The apparatus of claim 42, wherein the motor is a hydraulic motor having vanes for driving the hydraulic motor in response to hydraulic fluid flow against the vanes.
44. The apparatus of claim 42, wherein the vanes of the hydraulic motor are integral to the bone-sculpting tool.
- 25 45. The apparatus of claim 36, further comprising a flexible drive shaft for connecting the drive mechanism to a motor.
46. The apparatus of claim 42, wherein the motor is a surgical power drill.
47. The apparatus of claim 2, further comprising at least one additional bone-sculpting tool, the at least one additional bone-sculpting tool being configured
30 to mount on the mount or on an additional mount.
48. The apparatus of claim 1 or 2, further comprising an impaction apparatus for providing force between the second bone and the first bone, the impaction apparatus comprising an impaction device including an impaction attachment portion for attaching the impaction device to the second bone.
- 35 49. The apparatus of claim 48, wherein the impaction apparatus further comprises an adapter for mounting an implant.
50. The apparatus of claim 48, further comprising a visualization apparatus comprising a light source, an imaging base, an imaging device, and a display.

- 5 51. The system of claim 50, wherein the visualization apparatus further includes a monitoring system.
52. The apparatus of claim 50 or 51, wherein the imaging base is integral to a mount configured for attachment to the attachment portion of the bone-sculpting apparatus, the mount being attachable to the first bone.
- 10 53. The apparatus of at least one of claims 50 to 52, further comprising an irrigation apparatus integral to the imaging base.
54. The apparatus of at least one of claims 50 to 53, further comprising a suction apparatus integral to the imaging base.
55. The apparatus of claim 48, further comprising an irrigation apparatus.
- 15 56. The apparatus of claim 48 or 55, further comprising a suction apparatus.
57. The apparatus of claim 48 or 55 or 56, further comprising a surgical navigation system for positioning, aligning and monitoring the implant.
58. The apparatus of claim 48, further comprising a surgical navigation system for positioning, aligning and monitoring the impaction device.
- 20 59. An apparatus for replacing the surfaces of a joint between a first bone and a second bone, the first bone normally articulating in a predetermined manner with a second bone, the apparatus comprising:
- a first bone implant made up of a plurality of components configured for mimicking and replacing a bearing surface of the first bone; and
- 25 a second bone baseplate configured for mimicking and replacing a bearing surface of the second bone;
- wherein the components of the first bone implant and the second bone baseplate are joined within the confines of a joint cavity between the first bone and the second bone.
- 30 60. The apparatus of claim 59, wherein the plurality of components of the first bone implant and the second bone baseplate are aligned and oriented to each other within the confines of the joint cavity.
61. The apparatus of claim 59, wherein the baseplate further comprises a plurality of baseplate components.
- 35 62. The apparatus of claim 59, wherein the first bone implant comprises two components.
63. The apparatus of claim 59, wherein the first bone implant comprises three components.

- 5 64. The apparatus of claim 59, wherein the first bone is a femur and the second bone is a tibia and wherein the first bone implant is a femoral implant and the second bone baseplate is a tibial baseplate.
65. The apparatus of claim 59 or 64, wherein the baseplate is configured as a unitary piece.
- 10 66. The apparatus of claim 64 or 65, wherein the baseplate further comprises a fixed bearing attachment and a bearing attached thereto, and a mobile bearing attachment and a bearing attached thereto.
67. The apparatus of claim 64, wherein the baseplate includes separate baseplate components for the medial and lateral compartments of the tibia.
- 15 68. The apparatus of claim 61 or 67, wherein at least one of the baseplate components is fixed bearing.
69. The apparatus of claim 61 or 67, wherein at least one of the baseplate components is mobile bearing.
70. The apparatus of claim 61 or 67, wherein the baseplate components are a
20 combination of fixed bearing and mobile bearing.
71. The apparatus of claim 64, wherein the femoral implant comprises a first component for resurfacing the medial condyle and a second component for resurfacing the lateral condyle.
72. The apparatus of claim 71, wherein the second component also resurfaces
25 the patellofemoral groove.
73. The apparatus of claim 64, wherein the femoral implant comprises a first component for resurfacing the medial condyle, a second component for resurfacing the lateral condyle and a third component for resurfacing the patellofemoral groove.
- 30 74. The apparatus of claim 59 or 64, further comprising fins centrally located on each component of the implant for support.
75. The apparatus of claim 59 or 64, wherein each component further comprises a fin for driving into the first bone for implantation.
76. The apparatus of at least one of claims 59 to 63, or 64, wherein each
35 component has an inner surface and an outer surface and wherein the inner surface is comprised of a plurality of flexible segments.
77. The apparatus of claim 76, wherein the plurality of segments are bonded to an articular surface.

- 5 78. The apparatus of claim 76, wherein the outer surface is a thin sheet of implant grade material.
79. The apparatus of claim 76, further comprising a hardenable fluid for cementing the flexible segments.
80. The apparatus of claim 79, wherein the hardenable fluid is coated on each
10 component.
81. An apparatus for imparting force between first and second adjacent bones to secure an implant, the apparatus comprising:
- an impaction device including an attachment portion for attaching the
impaction device to the second bone; and
- an implant for securing to a first bone.
15
82. The apparatus of claim 81, further comprising an external alignment guide for orienting the implant.
83. The apparatus of claim 81, further comprising a surgical navigation system for positioning and aligning the implant with respect to the first bone.
- 20 84. The apparatus of claim 81, further comprising a surgical navigation system for positioning, monitoring and aligning the impaction device with respect to the first bone.
85. The apparatus of claim 81, further comprising a mount for attachment to the attachment portion, the mount being adapted for attachment to the second
25 bone.
86. The apparatus of claim 81, wherein the implant is an acetabular shell and the impaction device is configured to secure the acetabular shell in an acetabulum.
87. The apparatus of claims 81 or 86, further comprising an adapter for attaching
30 the implant to the impaction device.
88. The apparatus of claim 87, wherein the adapter restricts the implant from rotating.
89. The apparatus of claim 86, wherein the attachment portion is adapted for direct attachment to the second bone.
- 35 90. The apparatus of claim 86, wherein the attachment portion is adapted for indirect attachment to the second bone.
91. The apparatus of claim 81, wherein the impaction device is a pneumatic impaction hammer.

- 5 92. The apparatus of claim 81, wherein the impaction device is a linear actuator.
93. The apparatus of claim 81, wherein the impaction device is a hydraulic piston.
94. The apparatus of claim 81, wherein the impaction device is spring activated.
95. The apparatus of claim 81, wherein the impaction device is configured for
activation for a single impaction cycle for each activation.
- 10 96. The apparatus of claim 81, wherein the impaction device is configured for
activation for multiple impactions cycles while activated.
97. A method of sculpting the articular surface of a first bone that normally
articulates with a second bone, comprising the steps of:
- providing a bone-sculpting tool;
- 15 attaching the bone-sculpting tool to the second bone in a position for
sculpting the articular surface of the first bone; and
- sculpting the articular surface of the first bone by engaging the bone-
sculpting tool with the articular surface of the second bone.
98. The method of claim 97, wherein the step of sculpting the articular surface of
- 20 the first bone further includes the step of articulating one of the bones with
respect to the other bone.
99. The method of claim 97, further comprising the step of aligning the bone-
sculpting tool with the second bone .
100. The method of claim 99, wherein:
- 25 the step of attaching the bone-sculpting tool to the first bone comprises
attaching the bone-sculpting tool to a femur;
- the step of aligning the bone-sculpting tool with the second bone
comprises placing the bone-sculpting tool in the acetabulum; and
- the step of sculpting the articular surface of the second bone by
- 30 engaging the articular surface of the second bone comprises sculpting the
articular surface of the acetabulum by engaging the articular surface of the
acetabulum.
101. The method of claim 99 or 100, wherein the step of attaching the bone-
sculpting tool to the second bone includes attaching the bone-sculpting tool to
- 35 the second bone directly.
102. The method of at least one of claims 97 to 100, wherein the step of attaching
the bone-sculpting tool to the second bone includes attaching the bone-
sculpting tool to the second bone indirectly.

- 5 103. The method of claim 102, wherein the second bone is a femur and the first bone is an acetabulum and wherein the step of attaching the bone-sculpting tool to the second bone comprises the steps of attaching the bone-sculpting tool to a femoral trial and placing the femoral trial in the femur.
- 10 104. The method of claim 102, wherein the second bone is a femur and the first bone is an acetabulum and wherein the step of attaching the bone-sculpting tool to the second bone comprises the steps of attaching the bone-sculpting tool to a broach and placing the broach in the femur.
- 15 105. The method of claim 102, wherein the second bone is a femur and the first bone is an acetabulum and wherein the step of attaching the bone-sculpting tool to the second bone comprises the steps of attaching the bone-sculpting tool to a femoral implant and implanting the femoral implant in the femur.
- 20 106. The method of at least one of claims 97 to 102, wherein the step of attaching the bone-sculpting tool to the second bone further includes the steps of providing a mount for receiving the bone-sculpting tool and attaching the mount to the second bone with the bone-sculpting tool in a position for sculpting the articular surface of the first bone.
- 25 107. The method of claim 106, further comprising the step of providing an adjustable attachment for attaching the bone-sculpting tool to the mount.
- 30 108. The method of claim 107, further comprising the step of distracting the first bone from the second bone preoperatively to assess the range of motion of the second bone to the first bone and patient kinematics.
- 35 109. The method of claim 107, further comprising the step of distracting the first bone from the second bone during the step of sculpting the articular surface of the first bone.
110. The method of claim 109, wherein the step of distracting the first bone from the second bone includes allowing the second bone to hang freely from soft tissue attachments to the first bone during the step of sculpting the articular surface of the first bone.
111. The method of claim 108 or 109, further comprising the steps of providing a distractor and distracting the first bone from the second bone with the distractor.

- 5 112. The method of claim 111 wherein the distractor is expandable, and the step of distracting the first bone from the second bone further includes the step of expanding the distractor.
113. The method of claim 111 wherein the distractor is integral to the bone-sculpting tool.
- 10 114. The method of claim 100, further comprising the steps of elongating the bone-sculpting tool to engage the acetabulum and tensioning soft tissue structures spanning the joint.
115. The method of claim 100, further comprising the step of retracting the bone-sculpting tool to ease the step of placing the bone-sculpting tool within the
15 acetabulum.
116. A method of replacing the articular surfaces of a first bone that normally articulates in a predetermined manner with a second bone and replacing the articular surfaces of the second bone, comprising:
- 20 providing a bone-sculpting tool;
- 21 attaching the bone-sculpting tool to the second bone in a position for sculpting the articular surface of the first bone;
- 22 sculpting the articular surface of the first bone by engaging the bone-sculpting tool with the articular surface of the second bone;
- 23 providing an implant for replacing the articular surface of the first bone;
- 25 and
- 26 replacing the articular surface of the first bone with the implant.
117. The method of 116, further comprising the step of resecting a portion of the second bone to provide the second bone with a resected cavity and wherein the step of attaching the bone-sculpting tool to the second bone includes the
30 step of positioning the bone-sculpting tool within the resected cavity.
118. The method of claim 117, wherein the step of resecting a portion of the second bone includes advancing a cutting mill directly into the second bone.
119. The method of claim 116 or 117, further comprising the step of providing a mount wherein the step of attaching the bone-sculpting tool to the second
35 bone involves attaching the bone-sculpting tool to the mount and attaching the mount to the second bone.

- 5 120. The method of at least one of claims 116 to 119, wherein the step of sculpting the articular surface of the first bone includes the step of articulating one of the bones with respect to the other.
121. The method of at least one of claims 116 to 120, wherein the first bone implant comprises a plurality of components.
- 10 122. The method of claim 121, wherein each component of the first bone implant has an inner surface and an outer surface and wherein the inner surface is comprised of a plurality of flexible segments, and wherein the steps of placing the components of the first bone implant in the first bone resections further includes the step of providing a hardenable fluid along the first bone
- 15 resections and allowing the hardenable fluid to cure.
123. The method of claim 121, further comprising the step of articulating the second bone with respect to the first bone such that the second bone baseplate molds the flexible segments along the shape of the first bone resections.
- 20 124. The method of at least one of claims 116 to 123, further comprising the steps of providing a second bone baseplate and replacing the articular surface of the second bone with the second bone baseplate.
125. The method of claim 123, further comprising the step of joining the components of the first bone implant and the second bone baseplate within
- 25 the confines of the joint cavity.
126. The method of claim 125, wherein the step of joining further comprises aligning and orienting the components of the first bone implant and the second bone baseplate within the confines of the joint cavity.
127. The method of claim 116, further comprising the step of aligning the bone-
- 30 sculpting tool with the first bone.
128. The method of claim 116 or 127, further comprising the steps of providing an impaction apparatus comprising an impaction device configured for attachment to the second bone, attaching the impaction apparatus to the second bone, placing the implant on the impaction apparatus and imparting
- 35 force to the implant to secure the implant to the first bone, the force being reacted by the first bone and the second bone.

- 5 129. The method of claims 116, 127, or 128, further comprising the step monitoring the replacement of the articular surface with a monitoring device including a visualization apparatus, an irrigation apparatus, and a suction apparatus.
130. The method of claims 116, 127, or 128, further comprising the step of clearing the site of bone debris and blood using the irrigation apparatus and the
10 suction apparatus.
131. The method of claims 116, 127, or 128, further comprising the steps of bone preparation, positioning, aligning and monitoring the implant with a surgical navigation system.
132. The method of claim 128, further comprising the steps of positioning, aligning
15 and monitoring the impaction device with a surgical navigation system.
133. The method of claim 128, wherein:
the step of attaching the bone-sculpting tool to the first bone comprises
attaching the bone-sculpting tool to a femur;
the step of aligning the bone-sculpting tool with the second bone and
20 sculpting the articular surface of the second bone comprises placing the bone-sculpting tool within an acetabulum and sculpting the articular surface of the acetabulum;
the step of attaching the impaction apparatus mount to the first bone
comprises attaching the impaction apparatus mount to a femur;
25 and the step of imparting force to the implant comprises imparting force to an acetabular shell for securing the acetabular shell to the acetabulum, the force being reacted by the acetabulum and the femur.
134. A method of securing an implant to a second bone that articulates with a first bone, the method comprising the steps of:
30 providing an impaction device;
attaching the impaction device to the first bone;
placing an implant on the impaction device and aligning the implant with the second bone; and
imparting force to the implant, the force being reacted with the second
35 bone and the first bone.
135. The method of claim 134, wherein the step of imparting force is performed once per activation cycle.

- 5 136. The method of claim 134, wherein the step of imparting force is performed multiple times per activation cycle.
137. The method of claim 134, further comprising the steps of positioning, aligning and monitoring the acetabular shell with a surgical navigation system.
138. The method of claim 134, further comprising the steps of positioning, aligning and monitoring the impaction device with a surgical navigation system.
- 10 139. The method of claim 134, wherein:
the step of attaching the impaction device to the first bone comprises attaching the impaction device to a femur;
the step of placing an implant on the impaction device and aligning the
15 implant with the second bone comprises placing an acetabular shell on the impaction device and positioning the acetabular shell within an acetabulum;
and
the step of imparting force to the implant comprises imparting force to the acetabular shell, the force being reacted by the acetabulum and the
20 femur.
140. The method of claim 139, wherein the step of attaching the impaction device to the femur includes attaching the impaction device directly to the femur.
141. The method of claim 139, wherein the step of attaching the impaction device to the femur includes attaching the impaction device indirectly to the femur.
- 25 142. The method as in claim 141, wherein the step of attaching the impaction device to the femur comprises the steps of attaching the impaction device to a femoral trial and placing the femoral trial in the femur.
143. The method of claim 141, wherein the step of attaching the impaction device to the femur comprises the steps of attaching the impaction device to a
30 broach and placing the broach in the femur.
144. The method of claim 141, wherein the step of attaching the impaction device to the femur comprises the steps of attaching the impaction device to a femoral implant and implanting the femoral implant in the femur.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 6

Figure 7




Figure 8

Figure 9




Figure 5




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16




Figure 17




Figure 18




Figure 19




Figure 20




Figure 27




Figure 21




Figure 22




Figure 23




Figure 24




Figure 25




Figure 26




Figure 28




Figure 29



Figure 30






Figure 31






Figure 34




Figure 35




Figure 36





Figure 3.9




Figure 40




Figure 41




Figure 44




Figure 42




Figure 45

(fix element numbers
for 41, 42)




Figure 43




Figure 46






Figure 48









FIGURE
50






FIGURE : 5a





FIGURE 54



FIGURE

55





FIGURE 56



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 December 2002 (27.12.2002)


PCT

(10) International Publication Number
WO 02/102254 A3

- (51) International Patent Classification⁷: **A61B 17/16**, A61F 2/38
- (21) International Application Number: PCT/US02/18742
- (22) International Filing Date: 14 June 2002 (14.06.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/882,591 14 June 2001 (14.06.2001) US
10/075,829 12 February 2002 (12.02.2002) US
- (71) Applicants and
(72) Inventors: ENGH, Gerard [US/US]; 9409 Ludgate Drive, Alexandria, VA 22309 (US). JOHNSON, Wesley, D. [US/US]; 8091 Spruce Trail, Eden Prairie, MN 55347 (US).
- (74) Agents: MILLS GRIFFIN, Alicia et al.; Fredrikson & Byron, P.A., 4000 Pillsbury Center, 200 South Sixth Street, Minneapolis, MN 55402 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- (88) Date of publication of the international search report: 22 May 2003

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR SCULPTING THE SURFACE OF A BONE JOINT



(57) Abstract: The present invention provides a method and device for restoring individual patient joint kinematics using minimally invasive surgical procedures. The instrumentation of the invention sculpts the articular surface of a first bone that normally articulates in a predetermined manner with a second bone. The instrumentation includes a bone sculpting tool and a mount for attaching the tool to the second bone. The implant system is comprised of implants that provide intraoperative surgical options for articular constraint and facilitate proper alignment and orientation of the joint to restore kinematics as defined by the individual patient anatomy.

WO 02/102254 A3



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

PCT/US 02/18742

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 A61B17/16 A61F2/38

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No. .
X	US 4 574 794 A (T.D.COOKE ET AL.) 11 March 1986 (1986-03-11)	1-6,8,9, 21, 23-25, 27, 33-37, 39-45,47 12-20,46
Y	column 2, line 42 - line 58 column 2, line 67 -column 3, line 22 column 3, line 39 -column 4, line 5 figures 1,2	
X	US 4 457 307 A (W.T.STILLWELL) 3 July 1984 (1984-07-03)	1-6,8,9, 21,33, 34,36, 37, 39-45,47
A	figures 9,10	28
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

12 February 2003

Date of mailing of the international search report

20.02.2003

Name and mailing address of the ISA
 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Nice, P

INTERNATIONAL SEARCH REPORT

PCT/US 02/18742

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 231 611 B1 (R.MOSSERI) 15 May 2001 (2001-05-15) column 5, line 48 -column 6, line 6; figures 6-8 column 6, line 7 - line 18; figures 9-13 column 6, line 31 -column 7, line 17 ----	7,10,11, 22,38, 48-51, 57,58, 81,82, 85-87, 89,90, 92,95
Y	US 6 197 064 B1 (T.G.HAINES AND D.B.GOLDSTEIN) 6 March 2001 (2001-03-06) abstract; figures 3-5,7 ----	12-20,46
A	US 5 331 975 A (P.M.BONUTTI) 26 July 1994 (1994-07-26) abstract column 4, line 51 - line 52; figures 11-11A column 9, line 53 - line 67 ----	26
A	WO 99 59669 A (V.E.BRYAN) 25 November 1999 (1999-11-25) abstract; figure 2 ----	26
A	US 5 669 914 A (BOARD OF REGENTS OF THE UNIVERSITY OF COLORADO) 23 September 1997 (1997-09-23) column 4, line 45 - line 53 column 9, line 18 - line 52 figure 1 ----	26
A	DE 28 30 566 A (GUSTAV NEUHÄUSER PRÄZISIONSWERKZEUGFABRIK) 24 January 1980 (1980-01-24) claim 1; figure 1 page 12, line 22 -page 15, line 20 ----	28,29
A	DE 200 21 494 U (DEPUY ORTHOPÄDIE) 29 March 2001 (2001-03-29) claim 1; figure 1 ----	28,29
A	DE 21 20 320 A (B.WEISSMAN) 9 November 1972 (1972-11-09) page 4, line 17 - line 24 page 5, line 27 - line 29; figures 2,3 ----	28,29
A	DE 296 09 632 U (D.FENNEN) 7 November 1996 (1996-11-07) claims; figures ----	48,81

	-/--	

INTERNATIONAL SEARCH REPORT

PCT/US 02/18742

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 474 560 A (W.L.ROHR) 12 December 1995 (1995-12-12) column 1, line 61 -column 2, line 14; figure 1 ---	48,81
X	US 4 838 891 A (P.-I.BRANEMARK) 13 June 1989 (1989-06-13) ---	59-62, 64-71, 74,75 72
Y	column 8, line 36 - line 47 column 8, line 52 -column 9, line 60 figures 4,11A-B ---	
X	FR 2 266 492 A (ATELIERS DE LA HAUTE-GARONNE-ETABLISSEMENTS AURIOL AND J.-M.AURIOL) 31 October 1975 (1975-10-31) page 5, line 6 - line 12 page 5, line 31 - line 37 page 5, line 40 -page 6, line 4 page 6, line 11 - line 18 figures 1,2A,3-4 ---	59-64, 67,68, 71,74,75
X	US 4 085 466 A (J.W.GOODFELLOW ET AL.) 25 April 1978 (1978-04-25) figure 2 ---	59-62, 64,67, 69,71
X	US 3 958 278 A (A.J.C.LEE AND R.S.M.LING) 25 May 1976 (1976-05-25) abstract; figures 1,2 ---	59,60, 62,64, 65,71, 74,75
X	US 4 340 978 A (F.F.BUECHEL AND M.J.PAPPAS) 27 July 1982 (1982-07-27) abstract; figures 1A-B column 7, line 33 - line 35; figures 45,46 ---	59-62, 64,65, 67,69,71
X	US 3 953 899 A (J.CHARNLEY) 4 May 1976 (1976-05-04) abstract; figure 7 ---	59-62, 64,67, 68,71
X	EP 1 099 430 A (WALDEMAR LINK) 16 May 2001 (2001-05-16) abstract ---	59,60, 62,64, 65,71
X	DE 19 64 781 A (WALDEMAR LINK) 8 July 1971 (1971-07-08) figure 4 ---	59-62, 64,67, 68,71

	-/--	

INTERNATIONAL SEARCH REPORT

PCT/US 02/18742

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	FR 2 589 720 A (J.M.AUBANIAC) 15 May 1987 (1987-05-15) page 3, line 14 - line 24; figures 5,7,9,11 -----	72

INTERNATIONAL SEARCH REPORT

PCT/US 02/18742

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 97-144
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by surgery
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

As a result of the prior review under R. 40.2(e) PCT,
no additional fees are to be refunded.

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☒ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-25,27,33-47

1.1. Claims: 1-11,21-25,27,33-45,47

Apparatus for attachment to one bone and sculpting another, where the sculpted bone may be the acetabulum

1.2. Claims: 12-20,46

Apparatus for attachment to one bone and sculpting another, where the sculpting tool is rotatable

2. Claim : 26

Apparatus for attachment to one bone and sculpting another, provided with a fluid-filled distractor

3. Claims: 28-32

Apparatus for attachment to one bone and sculpting another, where the sculpting tool is elongatable

4. Claims: 48-58,81-96

Apparatus for attachment to one bone and impacting an implant into another

5. Claims: 59-80

Joint prosthesis

Please note that all inventions mentioned under item 1, although not necessarily linked by a common inventive concept, could be searched without effort justifying an additional fee.

INTERNATIONAL SEARCH REPORT

PCT/US 02/18742

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4574794	A	11-03-1986 CA 1231017 A1	05-01-1988
US 4457307	A	03-07-1984 NONE	
US 6231611	B1	15-05-2001 FR 2749753 A1	19-12-1997
		EP 0910316 A1	28-04-1999
		WO 9747257 A1	18-12-1997
		US 2001012967 A1	09-08-2001
US 6197064	B1	06-03-2001 US 5879354 A	09-03-1999
		US 5755803 A	26-05-1998
		US 5810827 A	22-09-1998
		US 5514139 A	07-05-1996
		US 5643272 A	01-07-1997
		US 5597379 A	28-01-1997
		US 2002029038 A1	07-03-2002
		AU 2125797 A	02-09-1997
		EP 0888089 A1	07-01-1999
		WO 9729703 A1	21-08-1997
		AU 1961597 A	02-09-1997
		WO 9729704 A1	21-08-1997
		US 6056754 A	02-05-2000
		AU 686457 B2	05-02-1998
		AU 3543295 A	27-03-1996
		CA 2198915 A1	14-03-1996
		EP 0778751 A1	18-06-1997
		JP 10507107 T	14-07-1998
		WO 9607361 A1	14-03-1996
US 5331975	A	26-07-1994 US 5345927 A	13-09-1994
		US 2002095160 A1	18-07-2002
		US 5514153 A	07-05-1996
		US 6451042 B1	17-09-2002
		US 6102928 A	15-08-2000
		US 2003023260 A1	30-01-2003
		US 6277136 B1	21-08-2001
		US 5716325 A	10-02-1998
		US 5667520 A	16-09-1997
		US 6171236 B1	09-01-2001
		US 6171299 B1	09-01-2001
		US 6187023 B1	13-02-2001
		US 5860997 A	19-01-1999
		US 5707390 A	13-01-1998
		US 5888196 A	30-03-1999
		US 6017305 A	25-01-2000
		US 5197971 A	30-03-1993
		US 6358266 B1	19-03-2002
		US 5163949 A	17-11-1992
		US 5827318 A	27-10-1998
		US 5954739 A	21-09-1999
		US 6042596 A	28-03-2000
WO 9959669	A	25-11-1999 AU 4088399 A	06-12-1999
		EP 1098672 A1	16-05-2001
		WO 9959669 A1	25-11-1999
US 5669914	A	23-09-1997 NONE	

INTERNATIONAL SEARCH REPORT

PCT/US 02/18742

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 2830566	A	24-01-1980	DE 2830566 A1	24-01-1980
DE 20021494	U	29-03-2001	DE 20021494 U1	29-03-2001
DE 2120320	A	09-11-1972	DE 2120320 A1	09-11-1972
DE 29609632	U	07-11-1996	DE 29609632 U1	07-11-1996
US 5474560	A	12-12-1995	NONE	
US 4838891	A	13-06-1989	SE 450336 B	22-06-1987
			DE 3584143 D1	24-10-1991
			EP 0183669 A2	04-06-1986
			JP 1928729 C	12-05-1995
			JP 6057225 B	03-08-1994
			JP 61247449 A	04-11-1986
			SE 8405989 A	06-06-1986
			US 4911721 A	27-03-1990
FR 2266492	A	31-10-1975	FR 2266492 A1	31-10-1975
US 4085466	A	25-04-1978	GB 1534263 A	29-11-1978
			CH 597847 A5	14-04-1978
			DE 2550704 A1	26-05-1976
			FR 2290883 A1	11-06-1976
			IE 42356 B1	30-07-1980
			JP 1221365 C	26-07-1984
			JP 51116095 A	13-10-1976
			JP 58041855 B	14-09-1983
US 3958278	A	25-05-1976	GB 1509194 A	04-05-1978
			CH 591847 A5	30-09-1977
			IE 41014 B1	26-09-1979
US 4340978	A	27-07-1982	US 4309778 A	12-01-1982
			AT 7456 T	15-06-1984
			CA 1176004 A1	16-10-1984
			CA 1169201 A2	19-06-1984
			DE 3067826 D1	20-06-1984
			EP 0021421 A1	07-01-1981
			JP 1210110 C	29-05-1984
			JP 56083343 A	07-07-1981
			JP 58048180 B	27-10-1983
US 3953899	A	04-05-1976	GB 1462876 A	26-01-1977
			AU 6833274 A	30-10-1975
			CA 1020703 A1	15-11-1977
			CH 584537 A5	15-02-1977
			DE 2421045 A1	05-12-1974
			FR 2229382 A1	13-12-1974
			IE 39217 B1	30-08-1978
			JP 50027394 A	20-03-1975
			SE 405679 B	27-12-1978
			ZA 7402415 A	30-04-1975
EP 1099430	A	16-05-2001	EP 1099430 A1	16-05-2001
			AU 1276201 A	06-06-2001
			BR 0007429 A	16-10-2001

INTERNATIONAL SEARCH REPORT

PCT/US 02/18742

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 1099430	A	CN 1342060 T	27-03-2002
		WO 0134069 A1	17-05-2001
		EP 1139937 A1	10-10-2001
		HU 0105106 A2	29-04-2002
DE 1964781	A	08-07-1971	DE 1964781 A1
			08-07-1971
FR 2589720	A	15-05-1987	FR 2589720 A1
			15-05-1987
		AU 6624686 A	02-06-1987
		EP 0245410 A1	19-11-1987
		WO 8702882 A1	21-05-1987